#### UNITED STATES · DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED OMB NO 1004-0135 Expires. July 31, 2010

# Lease Serial No

NMNM074935

	S)

#### SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

If Indian, Allottee or Tribe Name

SUBMIT IN TRIE	PLICATE - Other instruc	tions on reverse side.	31,013	7. If Unit or CA/Agre	ement, Name and/or No	
1 Type of Well	8 Well Name and No. ELECTRA FEDERAL 24					
Oil Well Gas Well Oth	er					
2 Name of Operator		PHYLLIS A. EDWARDS		9. API Well No		
COG OPERATING LLC	E-Mail. pedwards@	conchoresources com		30-015-2	36272 <u> </u>	
3a Address 550 W. TEXAS SUITE 1300 MIDLAND, TX 79701		3b. Phone No. (include area code) Ph: 432-685-4340 Fx: 432-685-4399		10 Field and Pool, or WILDCAT; WO		
4. Location of Well (Footage, Sec., T	., R , M , or Survey Description	)		11 County or Parish,	and State	
Sec 15 T17S R30E NWNW 330FNL 330FWL 32.84075 N Lat, 103.96678 W Lon		JUL 10 2008		EDDY COUNT	Y, NM	
	,	OCD-ARTE	RIA			
12. CHECK APPE	ROPRIATE BOX(ES) TO	INDICATE NATURE OF N	N N J 6161 14	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
□ Notice of Intent □ Subsequent Report	☐ Acidize	Deepen Deepen	☐ Production (Start/Resume) ☐ Reclamation		☐ Water Shut-Off	
	Alter Casing	Fracture Treat			☐ Well Integrity	
	☐ Casing Repair	☐ New Construction	Recomplete		☑ Other	
☐ Final Abandonment Notice	Change Plans	Plug and Abandon	Tempor	arily Abandon .		
	Convert to Injection	☐ Plug Back	□ Water D	Disposal		
13. Describe Proposed or Completed Op- If the proposal is to deepen directions Attach the Bond under which the wo following completion of the involved testing has been completed. Final Al determined that the site is ready for f  COG respectfully requests pe	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation respondenment Notices shall be fil- final inspection.)  rmission to change setting	give subsurface locations and measure the Bond No. on file with BLM/BLA sults in a multiple completion or receded only after all requirements, including depth of 8-5/8? casing to +	A. Required submitted and true vol.  A. Required submitted in a su	ertical depths of all perti bsequent reports shall b new interval, a Form 31 n, have been completed	nent markers and zones. e filed within 30 days 60-4 shall be filed once	
External Casing Packer / DVT water flow @ 598?.	combo @ +/- 400? inside	e 13-3/8? casing ( set @ 444′	?) to shut of	ff		
Cement with 450 sx C w/ 2% ppg, 1.34 yield on 2nd stage.	Cacl2, 14.8 ppg, 1.34 yiel	d 1st stage and 200 sx C w/ 2	2% Cacl2, 1	4.8		

## SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. Thereby certify that the foregoing is true and correct.  Electronic Submission #61288 verified by the BLM Well Information System  For COG OPERATING LLC, sent to the Carlsbad								
Name (Printed/Typed) PHYLLIS A. EDWARDS	Title	REGULATORY	REGULATORY ANALYST					
Signature (Electronic Submission)	Date	07/08/2008		APPF	ROVED			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved By	Title			JUL	9 2003 <sub>Dat</sub>	¢	_	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		;			W. INGRAM JM ENGINEER	3	_	

Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

### Electra Federal 24 COG Operating LLC July 9, 2008 Conditions of Approval

- 1. External casing packer/DVT combo to be set 50' above setting depth of surface shoe.
- 2. Cement behind 8-5/8" casing:
  - a. First stage to DV tool, cement shall:
  - Cement to circulate. If cement does not circulate, contact the appropriate BLM office, before proceeding with second stage cement job.
  - b. Second stage above DV tool, cement shall:
  - Cement to circulate. If cement does not circulate, contact the appropriate BLM office, before proceeding with second stage cement job.

WWI 070908