

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised June 10, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-32945
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name Mead
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		8. Well Number 004
2. Name of Operator Tom Brown, Inc.		9. OGRID Number 023230
3. Address of Operator P O Box 2608, Midland, TX 79702		10. Pool name or Wildcat Carlsbad; Morrow, South (Pro Gas) 73960
4. Well Location Unit Letter H : 2418 feet from the North line and 171 feet from the East line Section 5 Township 22S Range 27E NMPM County Eddy		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3153 GR		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded well on 10/15/03 @ 16:00 hrs. Drill 17-1/2" hole to 430'. On 10/16/03 ran 10 jts of 13-3/8" H-40 STC 48# casing (set @ 430'). Cement w/ 190 sx of Premium Light w/ 0.25#/sx Flocele and 1% CACL2 (12.5 ppg.; 1.97 yld) and 200 sx of Premium Plus w/ 2% CACL2 (14.8 ppg; 1.34 yld). Full returns throughout. Circulate 115 sx to pit. Bumped plug w/ 250 psi. Held. Cut off 13-3/8" casing. Weld on 13-3/8" SOW x 13-5/8" 3M psi well head. NU annular diverter system.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Diane Kuykendall TITLE Operations Asst/Tech DATE 10/20/03

Type or print name Diane Kuykendall E-mail address: dkuykendall@tombrown.com Telephone No. 432-688-9773

(This space for State use)

FOR RECORDS ONLY

APPROVED BY [Signature] TITLE [Signature] DATE OCT 27 2003

Conditions of approval, if any: Note WCC Time