

(REVISED)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED

OMB NO 1004-0137

Expires July 31, 2010

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

5 LEASE DESIGNATION AND SERIAL NO

NMLC-049998 (A)

1a Type of Well ☒ Oil Well ☐ Gas Well ☐ Dry ☐ Other
b Type of Completion ☒ New Well ☐ Workover ☐ Deepen ☐ Plug Back ☐ Diff Res

Other

2 Name of Operator

Marbob Energy Corporation

3 Address

P.O. Box 227
Artesia, NM 88211-0227

3a Phone No (include area code)

575-748-3303

6 INDIAN ALLOTTEE OR TRIBE NAME

7 UNIT AGREEMENT

8 FARM OR LEASE NAME

Foster Eddy #10

9 API WELL NO

30-015-26308

4 Location of Well (Report location clearly and in accordance with Federal requirements)*

At surface 2310' FNL & 1650' FWL, Unit F

At top prod Interval reported below

Same

At total depth

Same

NOV 12 2008

OCD-ARTESIA

14 Date Spudded

11/11/91

15 Date T D Reached

11/24/91

16 Date Completed

☐ D & A☒ Ready to Prod

10 FIELD NAME

Grayburg Jackson; SR-Q-Grbg-SA

11 SEC T. R. M. OR BLOCK AND SURVEY
OR AREA 17 T 17S R 31E

12 COUNTY OR PARISH

Eddy

13 STATE

NM

17. ELEVATIONS (DF, RKB, RT, GR, etc)*

3718.6'

GR

KB

18 Total Depth

MD

5580'

TVD

5580'

19 Plug back T D

MD

5542'

TVD

5542'

20 Depth Bridge Plug Set

MD

TVD

21 Type Electric & other Logs Run (Submit a copy of each)

SDSN, LML

22 Was well cored?

☒ No☐ Yes (Submit analysis)

Was DST run?

☒ No☐ Yes (Submit report)

Directional Survey?

☐ No☒ Yes (Submit copy)

23 Casing and Liner Record (Report all strings set in well)

Hole Size	Size/ Grade	Wt (#/ft)	Top (MD)	Bottom(MD)	Stage Cementer Depth	No of Sks & Type of Cement	Slurry Vol (Bbl)	Cement Top*	Amount Pulled
17-1/2"	13-3/8"	54.5#	0	211'		225 sx C		Circ 35 sx	
12-1/4"	8-5/8"	24#	0	1348'		750 sx C		Circ 100 sx	
7-7/8"	5-1/2"	17#	0	5554'		1250 sx		Circ 145 sx	

24 Tubing Record

Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)
2-7/8"	5496'							

25 Producing Intervals

Formation	Top	Bottom	26 Perforation Record	Size	No of Holes	Perf Status
A) Grbg-SA-Yeso	2882'	5484'	See Attached			
B)						
C)						
D)						

27 Acid, Fracture Treatment, Cement Squeeze, Etc

Depth Interval	Amount and Type of Material
See Attached	

28 Production- Interval A

Date First Produced	Test Date	Hours Tested	Test Production	Oil Bbl	Gas MCF	Water Bbl	Oil Gravity Corr API	Gas Gravity	Production Method
1/10/92	1/11/92	24	→	78	50	250			Pumping
Choke Size	Tbg Press Flwg SI	Csg Press	24 Hr Rate	Oil Bbl	Gas MCF	Water Bbl	Gas Oil Ratio	Well Status	
			→						Producing

28a Production- Interval B

Date First Produced	Test Date	Hours Tested	Test Production	Oil Bbl	Gas MCF	Water Bbl	Oil Gravity Corr API	Gas Gravity	Production Method
			→						
Choke Size	Tbg Press Flwg SI	Csg Press	24 Hr Rate	Oil Bbl	Gas MCF	Water Bbl	Gas Oil Ratio	Well Status	
			→						

ACCEPTED FOR RECORD

NOV - 7 2008

JERRY FANT
PETROLEUM GEOLOGIST

Date First Produced	Test Date	Hours Tested	Test Production →	Oil Bbl	Gas MCF	Water Bbl	Oil Gravity Corr API	Gas Gravity	Production Method
Choke Size	Tbg Press Flwg SI	Csg Press	24 Hr Rate →	Oil Bbl	Gas MCF	Water Bbl	Gas Oil Ratio	Well Status	

Date First Produced	Test Date	Hours Tested	Test Production →	Oil Bbl	Gas MCF	Water Bbl	Oil Gravity Corr API	Gas Gravity	Production Method
Choke Size	Tbg Press Flwg SI	Csg Press	24 Hr. Rate →	Oil Bbl	Gas MCF	Water Bbl	Gas Oil Ratio	Well Status	

Sold

31. Formation (Log) Markers

Formation	Top	Bottom	Descriptions Contents, Etc	Name	Top
					Measured Depth
				Queen	2420'
				Grayburg	2740'
				San Andres	3128'
				Lovington	3240'
					TD 5580'

32 Additional remarks (include plugging procedure)

☐ Electrical/ Mechanical Logs (1 full set required) ☐ Geologic Report ☐ DST Report ☐ Directional Survey

☐ Sundry Notice for plugging and cement verification ☐ Core Analysis ☐ Other

Name (please print) **Jeannie Sillas** Title **Production Assistant**

Signature Shannel Silvas Date 4/25/08

(Form 3160-4, page 2)

MARBOB ENERGY CORPORATION

Foster Eddy #10

30-015-26308

Perforations & Treatment

2882-2888'	3703'	4853'	5123'
2940-2946'	3718'	4860'	5162'
3170-3180'	3727'	4863'	5169'
3388'	3762'	4865'	5175'
3396'	3767'	4867'	5232'
3402'	3782'	4873'	5256'
3419'	3799'	4891'	5260'
3422'	3802'	4893'	5286'
3430'	3838'	4898'	5293'
3432'	3842'	4929'	5296'
3435'	3845'	4931'	5425'
3442'	4756'	4932'	5444'
3451'	4781'	4934'	5465'
3484'	4791'	4939'	5479'
3493'	4792'	4955'	5480'
3498'	4802'	4956'	5484'
3506'	4810'	4973'	
3513'	4814'	4988'	
3676'	4824'	4992'	
3686'	4829'	4998'	
3698'	4842'	5104'	

12/9/91	Perfed csg 2882-5484'
12/10/91	Acdz perfs 5425-5484' w/500 gal 15% NE acid
12/10/91	Acdz perfs 5232-5296' w/500 gal 15% NE acid
12/11/91	Acdz perfs 5104-5175' w/500 gal 15% acid; acdz 4756-4998' w/2000 gal 15% NE acid
12/12/91	Acdz perfs 3676-3845' w/750 gal 15% NE acid; acdz perfs 3388-3513' w/750 gal 15% NE acid
12/13/91	Acdz perfs 3171-3179' w/400 gal 15% NE acid; acdz perfs 2882-2940' w/600 gal 15% NE acid
12/14/91	Frac perfs 5425-5484' w/500 bbls gel wtr & 147 sx 20/40 & 152 sx 12/20 sand
12/16/91	Frac perfs 5104-5296' w/40000 gal 40# gel wtr & 222 sx 20/40 & 442 sx 12/20 sand
12/18/91	Acdz perfs 4756-4998' w/54000 gal heated 40# gel wtr & 32000 gal heated 20% acid
12/19/91	Acdz perfs 3676-3845' w/27000 gal gel, 16000 gal 20% acid, 5000 gal 15% NE and 4000 gal wtr
12/23/91	Sqzd perfs 3484-3513' w/46 sx Class C w/2% CC
12/30/91	Acdz perfs 3388-3451' w/27000 gal heated 40# gel wtr & 16000 gal heated 20% NE acid, flushed w/5000 gal 15% NE acid & 4000 gal fresh wtr.
12/31/91	Frac perfs 3171-3179' w/20000 gal 40# gel wtr & 114 sx 20/40 sand
1/2/92	Frac perfs 2882-2948' w/40000 gal 40# gel wtr & 222 sx 20/40 & 442 sx 12/20 sand