Submit 3 Copies To Appropriate District Office District Energy, Minerals and Natural Resources	Form C-103 June 19, 2008
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
District II 1301 W. Grand Ave, Artesia, NM 88210 OIL CONSERVATION DIVISION	30-015-36421
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St Francis Dr., Santa Fe, NM 87505	V-5604
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Junior AWW State 8. Well Number
1. Type of Well: Oil Well Gas Well Other	8. Well Number
2. Name of Operator Yates Petroleum Corporation NOV 2 1 2008	9. OGRID Number 025575
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210	10. Pool name or Wildcat Wildcat; Wolfcamp
4. Well Location	
Surf-Unit Letter I : 2130 feet from the South line and BHL-Unit Letter L : 2270 feet from the South line and	150 feet from the East line 330 feet from the West line
Section 17 Township 16S Range 28E	NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3563'GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME	ŊŢ JOB j ··· 🔲
DOWNHOLE COMMINGLE	The state of the s
OTHER: OTHER: Produc	tion casing
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
10/13/08 – Set kickoff plug at 5850'-6250' with 200 sx Class "H" + 0.65% D65 + 0.1% D13 (yld 0.99, wt 17). Tagged cement at 5778'.	
10/16/08 – Decision made to re-plug hole and start over. Drilled out 1 more joint to get some rathole for the cement to fill to have better	
plug. Pumped 190 sx Class "H" + 0.65% D65 + 0.1% D13 (yld .99, wt 18.8). WOC. Tagged cement at 5629'. WOC. Dress cement	
plug to 5770'. 10/18/08 – Drilled cement from 5770'-5936'. Started to drill directionally.	
11/5/08 – Reached TD 7-7/8" hole 10,994'.	
11/7/08 – Set 5-1/2" 17# HCP-110 LT&C casing at 10,994'. Cemented with 650 sx 50/50 Poz + 0.2% D13 + 0.125#/sx D130 + 0.2%	
D167 + 10% D20 + 5% D44 + 0.2% D46 + 0.2% D65 (yld 2.47, wt 11.9). Tailed in with 650 sx PVL + 2% D112 + 30% D151 + 2% D174 + 0.2% D46 + 0.6% D65 + 1% S1 (yld 1.83, wt 13). Cement circulated to surface.	
ACCEPTED FOR RECORD	
Spud Date: 9/24/08 Rig Release Date: 11	/8/08 NOV 2-1-2008
	Gerry Guye, Deputy Field Inspector
I hereby certify that the information above is true and complete to the best of my knowledge and belief. NMOCD-District II ARTESIA	
SIGNATURE TITLE Regulatory Compliance Supervisor DATE November 19, 2008	
Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168 For State Use Only	
APPROVED BY:TITLE	DATE
Conditions of Approval (if any):	