

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

MAR 19 2009

Form C-103
June 19, 2008

RM

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-64061
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. VA-2067
7. Lease Name or Unit Agreement Name Boffin State Unit
8. Well Number 2
9. OGRID Number 025575
10. Pool name or Wildcat Undes. Floor Ranch; Pre-Permian 76730

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>F</u> : <u>1980</u> feet from the <u>North</u> line and <u>1600</u> feet from the <u>West</u> line Section <u>16</u> Township <u>9S</u> Range <u>27E</u> NMPM <u>Chaves</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3832'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Completion Operations ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/2/09 - TOC 500' Est.

2/3/09 - Perforated Strawn 6263'-6266' (12), 6276'-6280' (16), 6282'-6286' (16), 6292'-6296' (16) and Mississippian 6372'-6383' (44).

2/4/09 - Acidized Mississippian 6372'-6383' with 1500g 7-1/2% IC HCL with 66 ball sealers.

2/8/09 - Acidized Strawn 6263'-6296' with 1500g 7-1/2% IC HCL with 100 ball sealers.

2/16/09 - Set RBP at 6334'. Set 5-1/2" 15.5# AS-1 packer with 2.25" on/off tool at 6118'.

2/19/09 - Frac Strawn 6263'-6296' with CO2 foam 25# borate XL frac, 440 bbls fluid, 2500# 100 mesh sand, 46,300# 20/40 Ottawa.

2-7/8" tubing at 6118'.

Spud Date:

12/26/08

Rig Release Date:

1/19/09

ENTERED
3-23-09
JH

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE March 18, 2009

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Jacqui Reev TITLE DATE 3/20/09

Conditions of Approval (if any):