Form 3160-5 (April2004)

## UNITEDSTATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-ARTESIA	FORMA OM B N	PPROVED o 1004-0137
MAR 3 0 2009 Sease Se	Expires	March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.		NMLC069140		
		6. If Indian, Allottee or Tribe Name		
OUDING IN TRIPLICATE OF A CO.		7. If Unit or CA/Agreement, Name and/or No		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.		NMNM68294		
1 Type of Well		8. Well Name and No		
2. NameofOperator		BIG EDDY UNIT #160		
BOPCO, L.P.		9 API Well No		
3a. Address 3b. Phone No. (include area code)		30-015-36289		
P.O. Box 2760 Midland TX 79702 (432)683-2277		10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T, R, M., or Survey Description)		Indian Flats (Atoka)		
NENW, 1140' FSL. 1830' FEL, SEC. 10, T22S, R28E		11. County or Parish, State Eddy		
		· · · · · · · · · · · · · · · · · · ·	NM	
12. CHECK AP	PROPRIATE BOX(ES)TO INDICATE	NATURE OF NOTICE, I	REPORT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	X Acidize Deepen	Production (S	tart/Resume)	
Notice of Intent	AlterCasing FractureT	reat Reclamation	Well Integrity	
X Subsequent Report	Casing Repair New Cons	struction Recomplete	X Other P&A Morrow	
	Change Plans Plug and A			
Final Abandonment Notice	Convert to Injection PlugBack	Water Disposa	Atoka perfs	
following completion of the investing has been completed. Find determined that the site is ready BOPCO, LP respectfully 09/24-27/2008 MISU PU good cement to DV tool @ 12630'. Re-tag PBTD 10/01-03/2008 POOH w/shots, 12564'-12576', 36 sub. Set pkr @ 12460' w tbg. 10/04-07/2008 Swab wel 01/29/2009 RU Cudd; puw/56 bbls 2% KCL + fric FR @ 2 BPM/3700 #.  See attachment for remain 14 Thereby certify that the foregname (Printed/Typed) Valerie Truax	volved operations. If the operation results in a munical Abandonment Notices shall be filed only after of final inspection.)  wishes to report the addition of pure pure pure pure pure pure pure pure	Itiple completion or recompletion all requirements, including reclaiments in the wellbore as the bit, 6 DCs & RIH w/d to the total float collar w @ 12511'-12518', 2 PU baker Model D pkrout down. PU Baker Model pending evaluation. In reducer, tagged w/P	prod tbg to tag DV tool @ 7746'. Drill @ 12593'. Drill good cement to PBTD 1 shots. Perf @ 12522'-12529', 21 w/ tbg subs, profile nipple & pump out lodel E-36 seal assembly & RIH w/ prod rotechnics zero wash tracer. Displaced pumped additional 100 bbls 2% KCI +	
Min	in huse		ACCEPTED FOR RECORD	
Signature Ujum		Date 03/17/2009	MOULTED FOR NEGUND	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE				
A		Title	MAR 2 8 2009	
Approved by fany are	attached. Approval of this nation does not week	Title	Date	
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease			Him	
			BUREAU OF LAND MANAGEMENT	
Title 18 U S C Section 1001 and Title States any false, fictitious or fraud	tle 43 U S C Section 1212, make it a crime for aidulent statements or representations as to any	ny person knowingly and willful matter within its jurisdiction	ly to make to any department or lageney of the United	

02/04/2009 RU Cudd to acidize 12511'-12590' perfs w/ 5000 gals 7-1/2% Morrow acid. RD Cudd.

02/05-02/12/09 Swab well with no production success.

02/27/2009 MIRU Lucky Well Service. Tag PBTD @ 12630' FS. PU & cut short CCL strip across EOT & pkr. POOH w/ tools. LD JB & PU Owen Prem CIBP. RIH w/ same, set CIBP in bottom tbg sub @ 12475' FS. Dump bail 25 sxs Class H cement on top to abandon Morrow. POOH w/ tools & RD BWWC.

02/28/2009 Perf Atoka @ 11462'-11471', 49 shots. PU Baker pump out plug w/ pins, SN, tbg subs, nipple & Hornet pkr. RIH, set pkr @ 11160' w/ EOT @ 11198'. POOH w/ tools. RD SWS.

03/05/2009 RDPU & turn well to production.

03/16/2009 Well test flowing: 0 BO, 2 BW, 1061 MCF, TP 840 psi, LP 394 psi, CP 0 psi, 12/64" choke.