

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

APR -7 2009

FORM APPROVED
Budget Bureau No 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NMNM09003

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
NM 71152

8. Well Name and No.
Sweeney Federal No. 1

9. API Well No.

30-015-10397

10. Field and Pool, or Exploratory Area
Lusk Delaware

11. County or Parish, State
Eddy, NM

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Lynx Petroleum Consultants, Inc.

2. Address
P.O. Box 1708, Hobbs, NM 88241

Telephone No.
505-392-6950

3. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660' FSL & 760' FWL
Section 13, T19S, R31E

12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **PLUG & ABANDON**

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

3/5/09 - 3/10/09

1. MIRU. NU BOP.
2. TIH to CIBP @ 4820'. Circulate hole w/gelled mud laden fluid. Spot 60 sx plug on top of CIBP. Tag cement @ 3951' (intermediate shoe @ 4001').
3. Cut and recover 3000' 4 1/2" csg.
4. Spot 30 sx plug across 4 1/2" stub (3050-2935'). Tried to circulate csg. Circulate with brine gel. Spot 50 sx. plug, never circulated. Tagged top of plug @ 2941'.
5. Spot 35 sx plug 2308-2188'.
6. Cut and recover 1500' 8 5/8" csg.
7. Spot 60 sx plug across 8 5/8" stub (1567-1454'). Tag top of plug @ 1454'.
8. Spot 60 sx plug 973-873'.
9. Spot 60 sx plug across 13 3/8" shoe (720-605'). Tag top of plug @ 605'.
10. Spot 60 sx plug at surface.
11. Erect dry hole marker. Cut off anchors and clean location.

Approved as to plugging of the well bore.
Liability under bond is retained until
Surface restoration is completed.

APPROVED

APR 4 2009

JAMES A. AMOS
SUPERVISOR-EPS

14. I hereby certify that the foregoing is true and correct

Signed Debbie M. Kelvey Title AGENT Date 3/23/2009

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any