

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St. Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

APR 15 2009

Form C-103
May 27, 2004

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	7. Lease Name or Unit Agreement Name: Empire Abo Unit "H"
2. Name of Operator BP America Production Company	8. Well Number 20
3. Address of Operator P.O. Box 1089 Eunice NM 88231	9. OGRID Number 00778
4. Well Location Unit Letter <u>P</u> : <u>330</u> feet from the <u>S</u> line and <u>990</u> feet from the <u>E</u> line Section <u>36</u> Township <u>17S</u> Range <u>27E</u> NMPM County <u>Eddy</u>	10. Pool name or Wildcat Empire Abo
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3662' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/6/09: TEST CSG TO 500 PSI. TEST GOOD. ND WELLHEAD. NU SPOOL, BOP & STRIPPER HEAD. FOUND TBG & PKR IN HOLE. NOT A CIBP. RELEASE PKR. POH LAYING DOWN 85 JTS 2 3/8" TBG.
4/7/09: POH LAYING DOWN TBG. RIH W/CIBP ON 2 3/8" TBG. SET @ 5457'. LOAD CSG W/6 BBL FRESH WATER. TEST TO 500 PSI. TEST GOOD. DISPLACE CSG W/FRESH WATER. SPOT 25 SX CMT FROM 5474' TO 5100'. LAY DOWN 14 JTS TBG. REV CIRC W/25 BBL FRESH WATER.

Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 4/13/09
Type or print name Barry C. Price E-mail address: barry.price@bp.com
Telephone No. 575-394-1648

For State Use Only

APPROVED BY [Signature] TITLE _____
Conditions of Approval, if any:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

DATE 4/16/09

Form C-103
Empire Abo Unit H-20
30-015-00677
Continued from Page 1

4/8/09: SPOT 28 1/2 BBL MUD FROM 5100' TO 3350'. POH LAYING DOWN 66 JTS & STANDING 48 STANDS. RU WIRELINE. RIH & PERF CSG @ 3350'. POH & RD WIRELINE. RIH W/PKR ON 2 3/8" TBG. SET @ 2820'. EST INJ RATE OF 2 BPM @ 1000 PSI. MIX & PUMP 100 SX CMT. DISPLACE W/14.5 BBL FRESH WATER.

4/9/09: RELEASE PKR. RIH & TAG CMT @ 2980'. DISPLACE CSG W/MUD FROM 2980' TO 1150'. LAY DOWN TBG & PKR.

4/10/09: RIG UP WIRELINE, RIH & PERF @ 1150'. POH & RIG DOWN WIRELINE. PUMP ON 4 1/2" CSG. BREAK CIRCULATION OUT 8 5/8" CSG W/25 BBL FRESH WATER. ND BOP. NU WELLHEAD FLANGE. MIX & PUMP DOWN 4 1/2" CSG & OUT 8 5/8" CSG W/400 SX CMT. CIRC. TO SURFACE. GOOD CMT OUT OF 8 5/8" CSG.

4/13/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, BACKFILL AND LEVEL LOCATION.