

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

JUN - 8 2009

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-34111

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
WYLIE

8. Well Number #2

9. OGRID Number 255333

10. Pool name or Wildcat
Artesia, Glorieta-Yeso (96830) - Existing
Red Lake, Queen-Grayburg-San Andres
(51300) - New

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter A : 990 feet from the NORTH line and 990 feet from the EAST line
Section 28 Township 17-S Range 28-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3641' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Open San Andres ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Lime Rock would like to open the San Andres in this existing Yeso oil well as follows:

TOH w/rods, pump, & tbg. Set a 5-1/2" RBP above the existing Yeso perfs (3442'-72") @ 3390'. PT 5-1/2" csg to 500-1000 psi. Perf San Andres @ about 2805'-3240'. Break down the new San Andres perfs w/about 5000 gal 15% NEFE acid & frac w/about 150,000# 16/30 & 60,000# 12/20 sand in 25# X-linked gel. Clean out after frac. Run production tbg, pump & rods & initiate pumping San Andres only. The existing Yeso perfs will remain shut-in below the RBP. We may apply for a commingle order in the future.

Spud Date: 5/17/06

Rig Release Date: 5/26/06

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 6/5/09

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: Jacqui Reas TITLE Geologist DATE 6/9/2009
Conditions of Approval (if any)