

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SEP 21 2009

Form C-103
June 19, 2008

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-02205
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Water Injection		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Stephens & Johnson Operating Co		6. State Oil & Gas Lease No. 648
3. Address of Operator P O Box 2249, Wichita Falls, TX 76307		7. Lease Name or Unit Agreement Name: State 648 AC811
4. Well Location Unit Letter <u>B</u> : <u>480</u> feet from the <u>North</u> line and <u>1480</u> feet from the <u>East</u> line Section <u>10</u> Township <u>19S</u> Range <u>28E</u> NMPM County <u>Eddy</u>		8. Well Number 73
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 019958
		10. Pool name or Wildcat Artesia QN-GB-SA

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached Proposed Plug & Abandonment procedure

Approval Granted providing work
is complete by 12/25/09

**Notify OCD 24 hrs. prior
To any work done.**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Kincaid TITLE Petroleum Engineer DATE 9-17-2009

mkincaid@sloc.net

Type or print name William M. Kincaid E-mail address: mkincaid@sloc.net PHONE 940-723-2166

For State Use Only

APPROVED BY [Signature] TITLE DATE 9/25/09

Conditions of Approval (if any):

STEPHENS & JOHNSON OPERATING CO.
STATE 648 AC811 WELL NO. 73
API NO. 30-015-02205
EDDY COUNTY, NEW MEXICO

Well Data:

Total Depth: 2186'
PBSD: 2177'
Surface Csg: 8" csg set @ 570', no record of cement
Prod. Csg: 4 1/2" 11.6# set @ 2186', cement w/135 sx, TOC
calculated to be @ 1784' (assume 10" hole)
Perfs: 2001'-2049'

Note: CIBP set @ 1975'

Proposed Plug and Abandonment Procedure

1. TIH w/tbg to CIBP @ 1975' and circulate hole w/9.5 #/gal mud.
2. Pump 25 sx cement on top of CIBP @ 1975'. TOH w/tbg.
3. Cut off 4 1/2" csg @ 1600' and TOH w/csg.
4. TIH w/tbg to 1600' and pump 50 sx cement plug. Wait 3 hours and tag cement (est. TOC @ 1500').
5. Set bottom of tbg @ 700' and pump 100 sx cement plug. Wait 3 hours and tag cement (est. TOC @ 500').
6. Spot a 10 sx cement plug at the surface. Cut off wellhead and install P&A marker. *60' minimum Surface Plug.*
Per. & Sguz. @ 60'