

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 June 19, 2008

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-31552
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-5862
7. Lease Name or Unit Agreement Name AID 24P State
8. Well Number 3
9. OGRID Number 255333
10. Pool name or Wildcat San Adres/Yeso
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,697' GR

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Lime Rock Resources A, L.P.

3. Address of Operator
Heritage Plaza, 1111 Bagby St. Suite 4600, Houston, TX 77002

4. Well Location
 Unit Letter: K: 1,860 feet from the South line and 1,650 feet from the West line
 Section 24 Township 17S Range 28E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Current Condition:

8-5/8", 24#, J-55 Casing set @ 639'. Cemented with 550 sxs to surface.
 5-1/2", 15.5#, K-55 Casing set @ 4,237'. Cemented with 745 sxs to surface.
 Perfs: 2,596-3,197'

Temporarily Abandon well as follows:

Pull rods, pump, and tubing. Set CIBP @ 2,550'. Place 35' cement on top of plug. Circulate casing with salt water and test to 500#. Install tubing sub and valve. Work should be performed as soon as OCD approval is received.

CAP CIBP @ 3730' w/ 35' CEMENT
 ON TOP OF PLUG.
 RE


CAN BE TA'D FOR 5 YEARS.
 RE

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. Tim Miller TITLE Vice President - Operations DATE 10/10/2009

Type or print name C. Tim Miller E-mail address: tmiller@limerockresources.com PHONE: (713) 292-9514

APPROVED BY: Richard Ince TITLE Compliance Officer DATE 10/01/09
 Conditions of Approval (if any):



8-5/8", 24#, K-55, ST&C Casing @ 639'

PROPOSED WELLBORE FOR TA STATUS

CIBP to be set @ 2,550' w/ 35' cement on top of plug

San Andres Perfs: 2,596-3,197' (35 holes)

CIBP @ 3,730'

Yeso Perfs: 3,768-08' & 3,872-70' (4 SPF)

PBTD @ 4,155'

5-1/2"; 15.5#, K-55; ST&C Casing @ 4,250'

TD @ 4,280'

**Lime Rock Resources
AID 24P State 23
Sec 24-17S-28E
Eddy County, NM**