Energy   Minerals and Natural Resources	Submit 3 Copies To Appropriate District	State of New M	evico	UCI U 5 Z(	Form C-103
MELL API NO.   Spanse   Distance   Marco   Distance	Office			,	
District		Energy, Willierars and Nat	urar Resources	WELL API NO.	171dy 27, 2004
1220 South St. Francis Dr.   Sunta Fe, NM 87505	District II	OIL CONSERVATION	IDIVISION		
STATE   FEE			· · · · · · · · · · · · · · · · · · ·		
12.03 St   Fances Dr. Stanie Fr. NM   20.00 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEBPIN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH   1	1000 Rio Brazos Rd., Aztec, NM 87410	1000 Rio Brazos Rd. Aztec NM 87410			
SUNDRY NOTICES AND REPORTS ON WELLS   CON NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFERENCE WELLS BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SCCH   R. Well Number   1		Santa Fe, INIVI o	7303	6. State Oil & Gas	Lease No.
DOND TUSE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFERNOR PLUG BACK TO A DIFFERENT RESERVOR. US. "PAPICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)  1. Type of Well: Oil Well   Gas Well Other   9, OGRID Number   14744   10, Pool name or Wildcat   10, Pool					
DIFFERENT RESERVOIR USE 'APPLICATION FOR PIEMMIT' (FORM C-101) FOR SUCH   S. Well Number   1   1   2   2   2   2   2   3   4   2   4   4   4   4   4   4   4   4					Unit Agreement Name
ROPOSALS)   1. Type of Well: Oil Well   Gas Well Other   1				*	
2. Name of Operator   10. Pool name or Wildcat   14744   3.3 Address Operator   10. Pool name or Wildcat   N Seven Rivers; Glorieta Yeso   97565   4. Well Location   10. Pool name or Wildcat   N Seven Rivers; Glorieta Yeso   97565   4. Well Location   Unit Letter   H : 2310   fect from the   N   line and   330   feet from the   E   line   Section   15   Township   208   Range   25E   NMPM   Eddy   County   S429 GL   Pitor Below-grade 1 mA Application   3429 GL   Pitor Below-grade 1 mA Application   3429 GL   Pitor Below-grade 1 mA Application   3429 GL   Pitor Below-Grade Tank Volume   bibs: Construction Material   12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data   NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:   REMEDIAL WORK   PLUG AND ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS   PAND A   PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB   X   OTHER:   13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RUILE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.   09/24/09   TDed 7 %" hole @ 3170. Ran 3170 4 ½" 11.6# J55 LT&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #g w' 1.54 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.   09/29/09. TDed 7 %" hole @ 3170. Ran 3170 4 ½" 11.6# J55 LT&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.8 #g w' 1.34 yd. Plug down @ 5:15 pm 09/29/09. To 20 Sks Cement op th. At 5:15 pm on 09/29/09. Sks Cement of the date of the best of my knowledge and belief. I further certify that any pit or below-grade tank has been-will be constructed or closed according to NMOCD guidelines   a general permit   or an (attached)	PROPOSALS)		ok see		
Mewhourne Oil Company		as Well Other			
10. Pool name or Wildcat   PO Box \$270   Hobbs, NM \$8240   N Seven Rivers; Glorieta Yeso 97565					,
PO Box 5270   Hobbs, NM 88240   N Seven Rivers; Glorieta Yeso 97565					/ildoot
Well Location					
Unit Letter H : 2310 feet from the N line and 330 feet from the E line Section 15 rowship 20S Range 25E NMPM Eddy County  11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3429 GL  Pit or Below-grade Tank Application or Closure   Pit type Depth to Groundwater Distance from nearest fresh water well bilstance from nearest surface water.  Pit Liner Thickness: mil Below-Grade Tank: Volume bbls: Construction Material  12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   ALTERING CASING   COMMENCE DRILLING OPNS.   P AND A    PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB X  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.  09/24/09MI & spud 11" hole. Ran 818' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.8 #g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.  09/29/09 TD'ed 7 %" hole @ 3170'. Ran 3170' 4 ½" 11.6# J55 LT&C csg. Cemented wi300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 14.8 #g w/ 1.34 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has betawill be constructed or closed according to NMOCD guidelines L1. a general permit   or an (attached) alternative OCD-approved plan    SIGNATURE THE Hobbs Regulatory DATE 10/01/09				14 Seven Rivers, Or	official reso 77303
Section   15   Township   20S   Range   25E   NMPM   Eddy   County   3429 GL   11. Elevation (Show whether DR, RKB, RT, GR, etc.)   3429 GL   Pit or Below-grade Tank Application   To Closure   Pit type   Depth to Groundwater   Distance from nearest fresh water well   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   mil   Below-Grade Tank: Volume   Distance from nearest surface water   Pit Liner Thickness:   Distance from nearest surface water   Pit Liner Thickness:   Mil Line Thickness:   Distance from nearest surface water   Distance from nearest su		0 0 0 0 0	1' 1 222	C-+ C 4 = =	1:
State   Stat		<del></del>	_		
SUBSEQUENT REPORT OF:   Pit Uner Thickness:   mil   Below-Grade Tank: Volume   bits:   Construction Material	Section 15				y County
Distance from nearest surface water   Distance from nearest fresh water well   Distance from nearest surface water   Distance from nearest surfa	Pit or Relow-grade Tank Application   or	3429' GL	, RKB, RT, GR, etc.)		
Pit Liner Thickness:   mil   Below-Grade Tank: Volume   bbls; Construction Material		<del></del>	vator wall Dista	anaa fram naarast surfaa	a water
NOTICE OF INTENTION TO:    SUBSEQUENT REPORT OF:   PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL WORK   ALTERING CASING     TEMPORARILY ABANDON   CHANGE PLANS   COMMENCE DRILLING OPNS.   P AND A     PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB   X     OTHER:   OTHER:   13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.    O9/24/09MI & spud 11" hole. Ran 818' 8 ½" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 ½" bit.    O9/29/09					e water
NOTICE OF INTENTION TO:    PERFORM REMEDIAL WORK					
PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  COMMENCE DRILLING OPNS.  PAND A  DULL OR ALTER CASING  MULTIPLE COMPL  CASING/CEMENT JOB X  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.  09/24/09MI & spud 11" hole. Ran 818' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minus, held OK. Drilled out with 7 %" bit.  09/29/09 TD'ed 7 %" hole @ 3170'. Ran 3170' 4 ½" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09 Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan SIGNATURE  ATTILE  DATE 10/01/09  Type or print name Jackie Lathan  E-mail address: jlathan@mewbourne.com Telephone No. 575-393-5905  For State Use Only  APPROVED BY:	12. Check A	ppropriate Box to Indicate N	lature of Notice, I	Report or Other D	ata
TEMPORARILY ABANDON	NOTICE OF INT	TENTION TO:	SUBS	SEQUENT REP	ORT OF:
OTHER:  OTHER	PERFORM REMEDIAL WORK	PLUG AND ABANDON 🔲	REMEDIAL WORK	(	LTERING CASING
OTHER:  OTHER	TEMPORARILY ABANDON ☐	CHANGE PLANS	COMMENCE DRIL	LING OPNS. T	AND A
OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.  09/24/09MI & spud 11" hole. Ran 818' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.  09/29/09 TD'ed 7 %" hole @ 3170'. Ran 3170' 4 ½" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \( \text{\	<del>-</del>	_		<del></del>	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.  09/24/09MI & spud 11" hole. Ran 818' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.  09/29/09 TD'ed 7 %" hole @ 3170'. Ran 3170' 4 ½" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \$\sum_\alpha\$ a general permit \$\sum_\alpha\$ or an (attached) alternative OCD-approved plan \$\sum_\alpha\$.  SIGNATURE TITLE Hobbs Regulatory DATE 10/01/09  Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com Telephone No. 575-393-5905  For State Use Only  APPROVED BY: DATE 10/13 2008	PULL OR ALTER CASING	MOLTIPLE COMPL	CASING/CEMENT	JOB X	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.  09/24/09MI & spud 11" hole. Ran 818' 8 %" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 %" bit.  09/29/09 TD'ed 7 %" hole @ 3170'. Ran 3170' 4 ½" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  1 hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \$\sum_\alpha\$ a general permit \$\sum_\alpha\$ or an (attached) alternative OCD-approved plan \$\sum_\alpha\$.  SIGNATURE TITLE Hobbs Regulatory DATE 10/01/09  Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com Telephone No. 575-393-5905  For State Use Only  APPROVED BY: DATE 10/13 2008	OTHER:		OTHER:		
14.6 #/g w/ 1.52 yd. Tail w/400 sks Class C with additives. Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 3:00 am 09/26/09. Circ 47 sks cmt to pit. At 4:30 pm 09/26/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 1/2" bit.  09/29/09 TD'ed 7 1/2" hole @ 3170'. Ran 3170' 4 1/2" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) with additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines \( \preceq\), a general permit \( \preceq\) or an (attached) alternative OCD-approved plan \( \preceq\).  SIGNATURE  TITLE Hobbs Regulatory  DATE 10/01/09  Type or print name  Jackie Lathan  E-mail address: jlathan@mewbourne.com  Telephone No. 575-393-5905  For State Use Only  APPROVED BY:  DATE 10/131 2009	of starting any proposed wor	k). SEE RULE 1103. For Multip			
additives. Mixed @ 11.5 /g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8 /g w/1.33 yd. Plug down @ 5:15 pm 09/29/09. Circ 95 sks cement to pit. At 5:15 pm on 09/29/09, tested csg to 1600# for 30 mins, held OK. Set wellhead slips w/35k.  09/29/09Released rig at 8:30 pm.  I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan  SIGNATURE	14.6 #/g w/ 1.52 yd. Tail w/400 sks C	Class C with additives. Mixed @	14.8 #/g w/ 1.34 yd.	Plug down @ 3:00 at	m 09/26/09. Circ 47 sks
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .  SIGNATURE  TITLE Hobbs Regulatory  DATE 10/01/09  Type or print name  Jackie Lathan  E-mail address: jlathan@mewbourne.com  Telephone No. 575-393-5905  For State Use Only  APPROVED BY:  DATE 10/13 2009	additives. Mixed @ 11.5 /g w/2.71 y	d. Tail with 350 sks Class C with	additives. Mixed @	) 14.8 /g w/1.33 yd. 1	Plug down @ 5:15 pm
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .  SIGNATURE  TITLE Hobbs Regulatory  DATE 10/01/09  Type or print name  Jackie Lathan  E-mail address: jlathan@mewbourne.com  Telephone No. 575-393-5905  For State Use Only  APPROVED BY:  DATE 10/13 2009	09/29/09Released rig at 8:30 pm.				
SIGNATURE  TITLE Hobbs Regulatory  Telephone No. 575-393-5905  For State Use Only  APPROVED BY:  DATE   0 13 2009	2 F				
SIGNATURE  TITLE Hobbs Regulatory  Telephone No. 575-393-5905  For State Use Only  APPROVED BY:  DATE   0 13 2009					
Type or print name Jackie Lathan E-mail address:jlathan@mewbourne.com Telephone No. 575-393-5905  For State Use Only  APPROVED BY: DATE 10/13/2009	I hereby certify that the information al grade tank has been/will be constructed or cl	pove is true and complete to the boosed according to NMOCD guidelines [	est of my knowledge ], a general permit [] o	and belief. I further o or an (attached) alternati	ertify that any pit or below- ve OCD-approved plan .
APPROVED BY: DATE 10/13/2009	SIGNATURE CELLO	Eathan TITLE H	obbs Regulatory	DA	ATE10/01/09
APPROVED BY: ACQUIP POR TITLE (gedonia) DATE 10/13/2009	· · · · · · · · · · · · · · · · · · ·	E-mail address:jla	athan@mewbourne.c	om Telephone	No. 575-393-5905
	To State Osc Only	1			
	APPROVED BY:	acqui bear TITLE	(redopio)		DATE 10/13/2009