OCD-ARTESIA

Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM	I AF	PR	OV.	ED
OMB I	No	100	4-0	137
Evoures	Ma	rch	31	200

FC	RM A	PPROV	/ED
ON	1B No	1004-0	0137
Г	16	1-21	0000

	OMB.	NO	1004-	uıs
	Expires	M	arch 31	, 20
one Carrel Me				

Lease Serial No	
	NM-102917

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an		6. If Indian, Allottee or Tribe Name			
abandoned well. Use Form 3160-3 (APD) for such proposals.					
SUBMI	T IN TRIPLICATE - Other in	nstructions on page 2.		7. If Unit of CA/Agree	ment, Name and/or No
I Type of Well		HECEIVE	$D \vdash$		
Oil Well Gas W	Vell Other	OCT 1 9 2009			RDX "21" #14
2. Name of Operator RKI Exploration	n & Production	NMOCD ADTE		9. API Well No.)-015-37112
3a. Address 3817 NW Expressway, Suite 950		H_Phone No. (mclude area-co	ale/A	10 Field and Pool or Exploratory Area Brushy Draw - Delaware	
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)		11. Country or Parish, State			
330' FNL & 9	330' FNL & 990' FEL Sec 21 T26S - R30E		Eddy Co. New Mexico		
12. CHEC	CK THE APPROPRIATE BOX	(ES) TO INDICATE NATUR	E OF NOTIC	CE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION		TY	PE OF ACT	ION	
Notice of Intent	Acıdize Alter Casıng	Deepen Fracture Treat		uction (Start/Resume)	☐ Water Shut-Off ☐ Well Integrity
Cubecouvert Donort	Casing Repair	New Construction		mplete	Other
✓ Subsequent Report	Change Plans	Plug and Abandon	Temp	porarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	☐ Wate	er Disposal	
determined that the site is ready for Work commenced in 8-24-09. Driller Found top of cement at 3605'.	•	cleaned out to 7242' (float co	ollar depth).	. Rigged up wire line u	unit and ran cement bond log.
Perforated Delaware 6740' to 6753'	-1 SPF =13 Holes, 6761' to	6773' -1 SPF =12 holes, 67	75' to 6782	' -2 SPF =14 Holes.	
Fracture stimulated via 5-1/2" casing	g at with 708 bbl. of X-linked	gelled water, 29557# 16/30) White san		
Perforated Delaware 6630' to 6648'	-2 SPF =36 Holes, 6613' to	6630' -1 SPF =17 Holes.		ACCE	PTED FOR RECORD
Fracture stimulated with 29,500 gal.	Conditions of	approval stated	6758# 16/3	0 Resin coated sand.	OCT 1.5 2009
Installed rod pump and test produced well. production casing cement was to overlap intermediate shoe by 200'. Submit plans for remedial cementing Within 20 december 19 CARL SBAD FIELD OFFICE				AU OF LAND MANAGEMENT ARI SBAD FIELD OFFICE	
14 I hereby certify that the foregoing is to Name (Printed/Typed) Gene Sir	the and co within 50 days	· 1 mus	·	Production Superin	
Signature Street	f. ime	Date /0-	6-09		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by	•				
Conditions of approval, if any, are attached that the applicant holds legal or equitable to entitle the applicant to conduct operations to	tle to those rights in the subject l			<u>. </u>	Date

Title 18 U S C Section 1001 and Title 43 U.S C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction