

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other2. Name of Operator
ConocoPhillips Company ATTN: Donna Williams3a. Address
P.O. Box 51810 Midland, Texas 79710-18103b. Phone No. (include area code)
432-688-68844. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit C, 660' FNL & 2480' FWL, Section 19, T-17-S, R-30-E

OCT 26 2009

NMOCD ARTESIA

5. Lease Serial No.

LC 028793-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

8. Well Name and No.

Grayburg Deep # 10

9. API Well No.

30-015-25796

10. Field and Pool, or Exploratory Area

Anderson (Pennsylvanian)

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection)

Set CIBP @ 10,729' Cap with 25sxs cmt
Spot 25sxs cmt @ 10,392'-10,089'
Spot 35sxs cmt @ 9,576'-9,223'
Spot 25sxs cmt @ 8,678'-8,425'
Spot 25sxs cmt @ 7,650'-7,397'
Perf @ 6,250' Sqz 40sxs cmt @ 6,250-6,150' WOC Tag
Perf @ 5,692' Sqz 40sxs cmt @ 5,692'-5,592' WOC Tag
Perf @ 4,155' Sqz 40sxs cmt @ 4,155'-4,055' WOC Tag
Perf @ 3,560' Sqz 40sxs cmt @ 3,560'-3,460' WOC Tag
Perf @ 2,762' Sqz 40sxs cmt @ 2,762'-2,672' WOC Tag
Perf @ 1,450' Sqz 40sxs cmt @ 1,450'-1,350' WOC Tag
Perf @ 479' Pump 180sxs cmt from 479' to surface out of 8 5/8" casing

SEE ATTACHED FOR
CONDITIONS OF APPROVALRECLAMATION PROCEDURE
ATTACHED14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Larry Winn

Title Area Manager, P&A Basic Energy Services 432-530-0907

Signature

Date

10/06/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

WOLF CAMP SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

Date September 9, 2009


RKB @ 3647'
 DF @ 3646'
 GL @ 3632'

Subarea Hobbs
 Lease & Well No Grayburg Deep # 10
 Legal Description 660' FNL & 2480' FWL, Sec 19, T17S, R30E
 Unit Letter "C"
 County Eddy State New Mexico
 Field Anderson (Pennsylvanian)
 Date Spudded 11/3/87 Rig Released 12/10/87
 API Number 30-015-25796
 Status:

Lease Serial No. LC-028793-A
 Agreement No. NM 70954A

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
	12/31/87	Perforate 2 SPF, 0 phasing; 10891-10895; 10912-10930 and 10947-10960						
		No stimulation Compl in Penn zone as flowing gas well						
		288 mcf @ 592 psi						
		Field Anderson Penn (Gas)						
	7/7/98	Re-perforated w/spiral phasing 4 SPF, 160 holes 10891-10895, 10912-10930 and 10947-10960						
	1/12/99	GIH w/ stim tube gun, shoot 10949-10957, 10916-10926 and 10893-10899 with 3 stimguns						
10891-10960	4/20/99	400 gal Claysafe w/N2 - Inc to 122 M						
10891-10960	4/21/99	Frac w/ 5,281# Carboprop down 2-7/8" Cleanout sand to 11,121' 775 Mscfd						
	6/27/08	Tag Fish @ 10902', mill to 11,115'						
	7/1/05	Set RBP @ 10,830'						
	7/11/05	Set Retainer @ 8550'; Squeeze w/300 sx Class H cmt						
	7/14/05	Drill out cmt, retrieve bridge plug						
	2/18/08	Requested to recomplete to Wolfcamp						



Formation Tops:

San Andres	2712'	Canyon	9253'
Glorieta	4105'	Strawn	10142'
Tubb	5642'	Atoka	10342'
Abo	6200'	Morrow	10562'
Wolfcamp	7600'	Mississippian	11020'
Cisco	8628'		

PBTD 11,192'
 TD 11,240'

WELLBORE SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian Operations

Date: September 9, 2009

RKB @ 3647'
 DF @ 3646'
 GL @ 3632'

Subarea Hobbs
 Lease & Well No. Grayburg Deep # 10
 Legal Description 660' FNL & 2480' FWL, Sec 19, T17S, R30E
Unit Letter "C"
 County: Eddy State New Mexico
 Field Anderson (Pennsylvanian)
 Date Spudded 11/3/87 Rig Released 12/10/87
 API Number 30-015-25796
 Status _____

Lease Serial No. LC-028793-A
 Agreement No. NM 70954A

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press.	ISIP	Max Rate	Max Down
	12/31/87	Perforate 2 SPF, 0 phasing; 10891-10895; 10912-10930 and 10947-10960						
		No stimulation Compl in Penn zone as flowing gas well 288 mcf/d @ 592 psi.						
		Field Anderson Penn (Gas)						
	7/7/98	Re-perforated w/spiral phasing 4 SPF, 160 holes 10891-10895, 10912-10930 and 10947-10960						
	1/12/99	GIH w/ stim tube gun, shoot 10949-10957, 10916-10926' and 10893-10899 with 3 stimguns						
10891-10960	4/20/99	400 gal Claysafe w/N2 - Inc to 122 M						
10891-10960	4/21/99	Frac w/ 5,281# Carboxprop down 2-7/8" Cleanout sand to 11,121' 775 Mscfd						
	6/27/08	Tag Fish @ 10902', mill to 11,115'						
	7/1/05	Set RBP @ 10,830'						
	7/11/05	Set Retainer @ 8550'; Squeeze w/300 sx Class H cmt						
	7/14/05	Drill out cmt, retrieve bridge plug						
	2/18/08	Requested to recompleat to Wolfcamp						

17-1/2" Hole

13-3/8" 61# @ 429'

Cmt'd w/500 sx, circ 200 sx

TOC @ Surface

11" Hole

8-5/8" 32# K-55 @ 3510'

Cmt'd w/ 2500 sx, circ 580 sx

TOC @ Surface

Top of Salt @

Base of Salt @

TOC 5-1/2" Csg @ 6800'

Sqz'd w/300 sx @ 8550'

Tight Spot @ 8593'

DV Tool @ 9526'

EOT @ 10,829'

Penn

10,891-10,898 (7', 2 SPF, 14 holes)

10,912-10,930 (18', 2 SPF, 36 holes)

10,947-10,960 (13', 2 SPF, 26 holes)

TOF @ 10,902', mill to 11,115'

7-7/8" Hole

5-1/2" 17# N-80, J-55 & K-55 @ 11,240'

Cmt'd w/ 1050 sx

TOC @ 6800' (Calc)

Formation Tops:

San Andres	2712'	Canyon	9253'
Gloneta	4105'	Strawn	10142'
Tubb	5642'	Atoka	10342'
Abo	6200'	Morrow	10562'
Wolfcamp	7600'	Mississippian	11020'
Cisco	8628'		

PBTD: 11,192'
 TD: 11,240'

Grayburg Deep #10
30-015-25796
Conoco Phillips Company
October 22, 2009
Conditions of Approval

Plugging Procedure:

1. Plug 1 – Spot 25 sxs Class H neat at 10,729' on top of CIBP at 10,729'.
2. Plug 2 – Spot 25 sxs Class H neat at 10,392'. Top of Atoka at 10,342'.
3. Plug 3 – Spot 25 sxs Class H neat at 9,576'. DV tool at 9,526'.
4. Plug 4 – Spot 25 sxs Class H neat at 8,678'. Top of Cisco at 8,628'.
5. Plug 5 – Perf. at 7,650' attempt to establish injection rate, if not established set plug 50' below perforations. Squeeze 40 sxs Class H neat. WOC tag plug at 7,475' or shallower. Top of Wolfcamp at 7,600'.
6. Plug 6 – Perf. at 6,250'. Sqz 40 sxs Class C neat. WOC tag plug at 6,090' or shallower. Top of Abo at 6,200'.
7. Plug 7 – Perf. at 5,692'. Sqz 40 sxs Class C neat. WOC tag plug at 5,537' or shallower. Top of Tubb at 5,642'.
8. Plug 8 – Perf. at 4,155'. Sqz 40 sxs Class C neat. WOC tag plug at 4,015' or shallower. Top of Glorieta at 4,105'.
9. Plug 9 – Perf. at 3,560'. Sqz 40 sxs Class C neat. WOC tag plug at 3,420' or shallower. Intermediate casing shoe at 3,510'.
10. Plug 10 – Perf. at 2,762'. Sqz 40 sxs Class C neat. WOC tag plug at 2,632' or shallower. Top of San Andres at 2,712'.
11. Plug 11 **moved** – Perf. at 1,122'. Sqz 40 sxs Class C neat. WOC tag plug at 1,012' or shallower. Top of Yates at 1,072'.
12. Plug 12 **moved** – Perf. at 500'. Sqz 180 sxs Class C neat. Additional cement may be required to bring the cement to surface, since the depth was changed. Top of Salt at 450'.
13. Install dry hole marker

CRW 102209

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

Permanent Abandonment of Federal Wells
Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 60th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.


6. **Dry Hole Marker:** All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. **Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

JDW 072709



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.
3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Environmental Protection Specialist
575-234-5909, 575-361-2648 (Cell)

Cody Layton
Natural Resource Specialist
575-234-5959

Terry Gregston
Environmental Protection Specialist
575-234-5958

Trishia Bad Bear
Natural Resource Specialist
575-393-3612

Bobby Ballard
Environmental Protection Specialist
575-234-2230

Todd Suter
Surface Protection Specialist
575-234-5987

Randy Rust
Environmental Protection Specialist
575-234-5943

Doug Hoag
Civil Engineering Technician
575-234-5979

Linda Denniston
Environmental Protection Specialist
575-234-5974

Jennifer Van Curen
Environmental Protection Specialist
575-234-5905

Justin Frye
Environmental Protection Specialist
575-234-5922