

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

RM

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-34134

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
NO BLUFF 36 STATE COM

8. Well Number #6

9. OGRID Number 255333

10. Pool name or Wildcat:
Red Lake, Glorieta-Yeso, NE
Red Lake, Queen-Grayburg-San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter D : 1125 feet from the NORTH line and 330 feet from the WEST line
Section 36 Township 17-S Range 27-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3566' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Recompleted to SA & Comgl w/Existing Yeso ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/9/09: MIRUSU. TOH w/rods, pump, & tbq. Set 5-1/2" CBP @ 2960' & PT csg to 5000 psi for 30 min - OK. Perfed lower SA @ 2471', 73', 74', 75', 77', 78', 79', 2511', 12', 16', 17', 18', 29', 30', 31', 58', 59', 60', 61', 63', 2609', 15', 16', 22', 23', 24', 45', 46', 2722', 24', 26', 28', 30', 31', 32', 33', 34', 36', 46', 47', 48', 49', 50', 52', 54', 55', 56', 58', 59', 60', 61', 62', 64', 65', 66', 67', 68', 69', 70', 72', 78', 79', 80', 2818', 19', 20', 34', 35', 36', 50', 51', 52', 61', 62', 82', 83', 98', 99', 2900' w/1-0.42" spf. Total 79 holes. Treated perfs w/2772 gal 15% NEFE acid & 150 perf balls. Fraced w/113,983# 16/30 & 44,269# 12/20 sand in 25# X-linked gel. Set 5-1/2" CBP @ 2424' & PT csg to 5000 psi for 30 min - OK. Perfed middle SA @ 2019', 20', 21', 30', 31', 32', 36', 37', 38', 39', 45', 46', 50', 51', 52', 69', 70', 2155', 56', 57', 58', 2212', 13', 14', 17', 18', 19', 39', 40', 41', 48', 49', 50', 57', 58', 59', 63', 64', 66', 68', 70', 71', 72', 73', 74', 75', 76', 77', 78', 79', 80', 81', 82', 84', 2304', 04', 06', 13', 14', 15', 16', 17', 35', 36', 37', 38', 39', 40', 41', 49', 50', 98', 2400', 01', 02', 03', 04', 05', 06' w/1-0.42" spf. Total 79 holes. Treated w/2772 gal 15% NEFE acid & 150 perf balls. Fraced w/88,758# 16/30 & 41,876# 12/20 sand in 25# X-linked gel. Drilled out CBPs @ 2424' & 2960' & CO to 3531'. Landed 2-7/8" 6.5# J-55 tbq @ 3463'. Ran pump & rods & started pumping load water. Released workover rig on 10/19/09. Completed well commingled as per order DHC-4210. Lime Rock plans to submit commingle allocations & calculations within 60 days.

Spud Date: 9/20/05

Drilling Rig Release Date: 10/1/05

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 10/23/09

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: Jaqueline TITLE Geologist DATE 10/29/2009
Conditions of Approval (if any):