


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA



FORM APPROVED
OMB No 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5 Lease Serial No
LC-067832-A

6 If Indian, Allottee or Tribe Name
NA

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1 Type of Well

☐ Oil Well ☐ Gas Well ☒ Other P&A

2 Name of Operator

Yates Petroleum Corporation

3a Address

105 S. 4th Str., Artesia, NM 88210

3b. Phone No (include area code)

575-748-1471

4 Location of Well (Footage, Sec., T., R., M., OR Survey Description)

1965'FNL & 1659'FEL of Section 20-T21S-R23E (Unit G, SWNE)

7 If Unit or CA/Agreement, Name and/or No

NMNM106836

8 Well Name and No

West Indian Basin Federal Com #2

9 API Well No

30-015-10282

10 Field and Pool or Exploratory Area

Indian Basin; Upper Penn

11 County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

10/21/09 MIRU. NU BOP. TIH with gauge ring to a depth of 7200'. Set a 5-1/2" 17# CIBP at 7188'.

10/22/09 Circulated hole with plugging mud from 7188' to surface. Spotted 25 sx Class "C" cement from 6988'-7188'. Spotted 25 sx Class "C" with 3% CC from 5560'-5760'. WOC.

10/23/09 Tagged cement at 5530'. Spotted 25 sx Class "C" cement from 2697'-2897'. Perforated 4 squeeze holes at 1932'. Attempted to pump into squeeze holes at 1932' at 500 psi. Unable to pump into squeeze holes. Dropped down to 1982'. Spotted 25 sx Class "C" cement with 3% CC from 1782'-1982'. WOC 3 hrs. Tagged cement at 1832'. Perforated 4 squeeze holes at 238'. Attempted to circulate down the 5-1/2" casing and up the 8-5/8" to braden head. Unable to circulate. Pumped into squeeze holes at 238' at .5 BPM @ 600 psi to 1100 psi.

10/26/09 Established pump rate into squeeze holes at 238' with fresh water at .5 BPM at 1100 psi. Pumped 25 sx Class "C" cement with 2% CC at 14.8 ppg down 5-1/2" casing and into squeeze holes at 238'. Displaced cement to 150'. WOC 3 hrs. Tagged cement at 150'. Perforated 4 squeeze holes at 100'. Unable to circulate down casing and up braden head. Pumped into squeeze holes at 1 BPM at 400 psi. Pumped 50 sx Class "C" cement with 2% CC at 14.8 ppg. Squeezed off at 800 psi. Cement standing full at surface. ND BOP. Cleaned location.

10/28/09 Cut off wellhead and installed dry hole marker as per BLM regulations. **WELL IS PLUGGED AND ABANDONED.**

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Tina Huerta

Title Regulatory Compliance Supervisor

Signature

Date October 30, 2009

Accepted as to plugging of the well hole. FEDERAL OR STATE OFFICE USE

Liability under bond is retained until
Surface restoration is completed.

Approved by

Title

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

