## Form 3160-5 RECEIVED

## UNITED STATES DEPARTMENT OF THE INTERIOR: ...

FORM APPROVED OMB NO. 1004-0135

	OMID NO. 1004-0155
	Expires: November 30, 200
5.	Lease Serial No.

BUREAU OF LAND MANAGEMENT							
IDRY NOTICES AND REPORTS ON WELLS							

NWC	OV 13 2003 SUNDRY NOTICES  OCD ART BSNA use this form for partial description of the superior	NM43744 6. If Indian,	NM43744 6. If Indian, Allottee or Tribe Name						
	SUBMIT IN TRIPLICATE - 0	7. If Unit or	7. If Unit or CA/Agreement, Name and/or No						
3a. Address P.O. 1 4. Location	Well Gas Well Other Operator SA Inc.	Description)			Sand Dune Federal 9. API Well 30-015-27 10. Field and	8. Well Name and No. Sand Dunes 34 #3 Federal 9. API Well No. 30-015-27240 10. Field and Pool, or Exploratory Area Ingle Wells Delaware			
330 1	3L 330 TEL 3L3L(F) 3eC 34 12.					11. County of Eddy	r Parisl	h, State	
	12. CHECK APPROPRIATE	BOX(ES) TO IN	DICATE	NATURE OF N	OTIC	E, REPORT, OR O	HER	DATA	
	TYPE OF SUBMISSION			TYP	PE OF A	ACTION			
If the	Notice of Intent  X Subsequent Report  Final Abandonment Notice  Tribe Proposed or Completed Operation (clearly e proposal is to deepen directionally or recompleth the Bond under which the work will be per	lete horizontally, give:	ails, inclu subsurfac	e locations and meas	ng date	d true vertical depths of	all perti	inent markers and zones.	
9/21/09 ( 9/22/09 ( 9/22/09 (	Pick up subs and 2 - 1" rods latch on to pump Unset pump pull 10,000 over rod weight to unset lay down subs ans 2 - 1' rods let equalize. Pull out of hole with 93 - 1 1/4 Fiberglass, 171 - 7/8 D78, 7/8 x 26K shear tool, 1 - 7/8 D78 rod, lay down fish and pump w/ GA Check tbg pressure 30 psi bleed off open well. Rig up sandline ran in with no/go tag SN @ 7,825' pulled out of hole lay down no/go ran in with sandline and bars tag MA jt @ 7,870' - 45' deeper with sandline depthometer lay down bars. Pick up 25-125-RHBC-20-4 pump with 20' x 1" dip tube 3' x 1" sand screen, 4' x 7/8 stabilize sub, 1 - 1 1/2 sinker bar, 3/4 x 26K shear tool, 3 - 1 1/2 sinker bars, ran in hole with 168 - 7/8 D78, 93 - Fiberglass rods.  Pick up 2'.4' x 1" pony subs install polish rod. Hang on pumping unit head. Space out pump 42' off bottom. BD RH Clean lock.								
9/28/09 I	to production. Pumped 10 BO 75BW 47MCFD  NOV 10 2009 NOV 10 Kristof								
Name (	y certify that the foregoing is true and correct Printed/Typed)		Т	itle Sr. Re	gulat	ORY ARTOLYS ARLSBA	D FIEL	O OFFILM	
	la Sat		D	ate ula	(09				
	THIS	SPACE FOR FE	DERAL	OR STATE OF	FICE L	JSE			
Approved	by ,			Title			Date		
certify that	of approval, if any, are attached. Approval of the applicant holds legal or equitable title to ld entitle the applicant to conduct operations the	those rights in the sul	warrant o oject leas	Office		M	<i>j</i>		