

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-37348

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Quick Draw 10 P

8. Well Number 1

9. OGRID Number
14744

10. Pool name or Wildcat
Cemetery Yeso

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator PO Box 5270
Hobbs, NM 88241

4. Well Location

Unit Letter P : 940 feet from the South line and 990 feet from the East line
Section 10 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3404'

RECEIVED

NOV 11 2009

NMOCD ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/04/09...MI & spud 11" hole. Ran 816' 8 3/8" 24# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed @ 14.6 #/g w/1.52 yd. Tail with 400 sks Class C with additives. Mixed @ 14.8/g w/1.34 yd. Plug down @ 12:45 pm 11/05/09. Circ 100 sks to pit. WOC 18 hrs. At 4:30 am 11/06/09 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 7 7/8" bit.

11/08/09 TD'ed 7 7/8" hole @ 3257'. Ran 3257' 4 1/2" 11.6# J55 LT&C csg. Cemented w/300 sks BJ Lite Class C (50:50:10) w/additives. Mixed @ 11.5#/g w/2.71 yd. Tail with 350 sks Class C with additives. Mixed @ 14.8/g w/1.33 yd. Plug down @ 12:01 am 11/09/09. Circ 103 sks cement to pit. At 12:01 am 11/09/09, tested csg to 1700# for 30 mins, held OK. Set wellhead slips w/30k.

11/09/09...Released rig at 6:00 am.

Spud Date: 11/04/09

Rig Release Date: 11/09/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 11/10/09

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 11/19/2009

Conditions of Approval (if any):