Submit 3 Copies To Appropriate District	State of New Mexico		Form C-103	
<u>Ďistrict I</u>	Energy, Minerals and Natural Resources		WELL API NO.	4
1625 N French Dr, Hobbs, NM 88240 <u>District II</u>	OIL CONSERVATION DIVISION		30 – 015 – 01649	
1301 W Grand Ave, Artesia, NM 88210 District III	1220 South St. Francis Dr.		13. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE STATE FEE	_
1220 S. St Francis Dr., Santa Fe, NM	2 Wallow 1 5, 1 111 2 6	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	B-2071	
87505 SUNDRY NOT	ICES AND REPORTS ON WELL	CEIVED	7. Lease Name or Unit Agreement Name	\dashv
(DO NOT LISE THIS FORM FOR PROP	SOLI CITO DOUL OD TO DECIDENTO		Empire Abo Unit "H"	
PROPOSALS)	JSALS TO DRILL OR TO DEEPEN OR THE ICATION FOR PERMIT" (FORM C-101) F	OR SUCH 2010	8. Well Number	\dashv
1. Type of Well: Oil Well	Gas Well		23	
2. Name of Operator	NMO perica Production Company	CD ARTESIA	9. OGRID Number 000778	
3. Address of Operator			10. Pool name or Wildcat	\dashv
P. O. I	Box 1089 Eunice, New Mex	rico 88231	Empire Abo	
13. Well Location				
Unit Letter O: 660 feet from the South line and 1939 feet from the East line				
Section 31 Township 17S Range 28E NMPM County Eddy				
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3696' GR				
Pit or Below-grade Tank Application	or Closure			7
Pit typeDepth to Groundy	vaterDistance from nearest fresh	water well Dista	nce from nearest surface water	
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Con	struction Material	
12. Chec	k Appropriate Box to Indicate	Nature of Notice,	, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				l
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A ☒				
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT		
OTHER:	<u>U</u>	OTHER:		_
			give pertinent dates, including estimated da	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
-	aguinment en 12/21/09. Het wat	orod down casing	backed off rods & POH. RU to strip tbg	و
			P. Fished tbg and stripped remainder	
			H w/ 5½" CIBP on tbg and set @ 5740	
			onto top of CIBP. Abo plug set fro	
5500' - 5740' on 1/5/10. Circ'd hole w/ 9.5 ppg mud laden fluid, LD tubing to 3612' and spotted 25 sx Class "C"				
across top of Glorieta @ 3467'. WOC overnight & tagged plug @ 3335'. Glorieta plug set from 3335' – 3612' on 1/5/10. LD tbg to 2259' and spotted 25 sx Class "C". Isolation plug across remedial squeeze perfs @ 2150' set				
from 2020' – 2259' on 1/6/10. LD tbg to 1254' and spotted 140 sx Class "C" to surface - good cement returned				
to surface inside 5½" csg. POH & LD all tbg - filled 5½" csg to surface w/ Class "C" after POH w/ tbg. This				
placed plug across 8 5/8" surface casing shoe @ 1200', across top of Queen @ 1189', across top of Yates @ 357' and set the top plug - final plug in place on 1/6/10. ND BOP and RD & MO equipment on 1/6/10. Cut-off well				
heads and guy wire anchors to 3' below GL, installed regulation Dry Hole Marker and completed wellbore P&A				
			laimed and ready for final inspection.	
I hereby certify that the information	above is true and complete to the h	est of my knowledge	and belief. I further certify that any pit or below	u _
grade tank has been/will be constructed or	r closed according to NMOCD guidelines	☐, a general permit ☐ o	r an (attached) alternative OCD-approved plan	•
SIGNATURE Jum Lud	TITLE Wells O	peration Superinten	dent DATE 1/18/10	_
Type or print name M. D. We	stmoreland E-mail address: _d	ian.westmoreland@l	bp.com Telephone No. 432 / 688-524	<u>5</u>
For State Use Only	/	Approved for plugging of	well bore only.	
APPROVED BY:		Liability under bond is ret	port of Well Plugging) DATE //21/2	2010
Conditions of Approval (if any):		which may be found at O	CD Web rage and	_
11 \ \ \ /.		Forms, www.cmnrd.state.i	11111.439.004.	
		Forms, www.cmnrd.state.	inin, day occi.	



Empire Abo Field

API No. 30-015-01649 State Lease No. B-2071

660' FSL & 1939' FEL Sec 31 - T17S - R28E Eddy County, New Mexico

Final P&A Status

1 / 14 / 10

Yates 337'

Shoe - Queen - Yates - Top Plug
0' - 1254'
140 sx Class "C"
Set 1/6/10

Queen 1189'

Spud 1/30/60 RR 2/20/60 P&A 1/6/10 Well Life 18,239 days

85/8" 22.7# @ 1200' w/ 550 sx to surface

Perf'd 5 1/2" @ 2150' cmtd w/ 500 sx - circ

Perfd 51/2" @ 2150'. cmtd w/ 500 sx - circ to surface TOC @ 2223' by CBL of 8/20/87

Isolation Plug 25 sx Class "C" 2020' - 2259' Set 1/6/10

Glorieta Plug 25 sx Class "C" 3335' - 3612' Set 1/5/10, tagged 1/6/10

Glorieta 3467'

Abo Plug 5500' - 5740' CIBP @ 5740' Capped w/ 25 sx Class "C" Set 1/5/10 6076' PBD 6094' TD

Perfs 5862' - 5876'

Perfs 5910' - 5960'

Perfs 6023' - 6060'