


OCD-ARTESIA

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other Instructions on page 2

1 Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		5 Lease Serial No. NMNM31636
2 Name of Operator Marbob Energy Corporation		6 If Indian Allottee or Tribe Name
3a Address PO Box 227 Artesia, NM 88211-0227		7 If Unit or CA Agreement Name and/or No.
3b Phone No. (include area code) (575) 748-3303		8 Well Name and No. Mule 23 Federal #1
4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 550 FSL 2215 FWL, Sec. 23-T24S-R25E, Unit N		9 API Well No. 30-015-35846
		10 Field and Pool, or Exploratory Area WC; Strawn
		11 County or Parish, State Eddy Co., NM

12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input checked="" type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input checked="" type="checkbox"/> Plug back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation (clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will be performed or provide the Bond No. on file with the BLM's BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamation have been completed, and the operator has determined that the site is ready for final inspection.)

Marbob Energy Corporation proposes to perforate, acidize, test & possibly frac the Penn zone as follows:

Set CIBP + 35' cmt at appx 10625'. (Zone to be abandoned: Strawn).

Penn 10084' (8 shots), 10221' (8 shots) 1800 gal NE Fe 7 1/2% HCl
10323' (8 shots), 10407' (8 shots)

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

Set CIBP + 35' cmt at appx 10050'.

Penn Lime 9764' - 9769' (12 shots) 1500 gal NE Fe 15% HCl

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Signature: Diana J. Briggs Title: Production Analyst
Date: December 21, 2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE
APPROVED
JAN 15 2010
s/ Dustin Winkler
BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any statement or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Marbob Energy Corporation
NM-31636: Mule 23 Federal #1
API: 30-015-35846
Eddy County, New Mexico

RE: Plug back and Recomplete NGL - Conditions of Approval

There is to be no surface disturbance beyond the existing pad. A closed loop system is to be used. H2S monitoring and protection equipment is to be on site.

Tag to verify depth of CIBP set at 11,530'. Should tag up 35' shallower because of bailed cement.

Submit subsequent report and completion report once work is completed.

DHW 010610