

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-36977
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STALEY STATE
8. Well Number #8
9. OGRID Number 255333
10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	RECEIVED MAR 10 2010 NMOCD ARTESIA
2. Name of Operator LIME ROCK RESOURCES A, L.P.	
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401	
4. Well Location Unit Letter J : 1980 feet from the SOUTH line and 2310 feet from the EAST line Section 30 Township 17-S Range 28-E NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3601' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: Glorieta-Yeso Payadd Workover ☒	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/9/10: MIRUSU. for rod job. Fished rods & pump & TOH w/tbg. Found severe scale on all tubulars. Using 4-3/4" bit, CO to 4805' on 2/13/10. Treated existing Yeso perfs 3610'-4619' w/total of 3000 gal 15% NEFE acid & scale inhibitor in 3 stages. Set 5-1/2" RBP @ 3590'. On 2/19/10, PT 5-1/2" csg & RBP to 4800 psi for 30 min-OK. Perfed additional Glorieta-Yeso @ 3226', 27', 36', 37', 43', 44', 60', 61', 84', 85', 86', 3302', 03', 09', 12', 13', 29', 30', 39', 40', 42', 43', 44', 64', 65', 66', 67', 68', 69', 70', 78', 84', 90', 92', 93', 94', 99', 3400', 01', 04', 05', 06', 09', 10', 18', 19', 20', 24', 25', 33', 34', 35', 36', 37', 44', 45', 59', 60', 66', 67', 70', 71', 99', 3503', 05', 13', 14', 15', 16' w/1-0.32" spf. Total 69 holes. Treated new perfs w/4500 gal 15% NEFE acid & 140 perf balls. On 2/23/10, fraced w/135,430# 16/30 & 50,145# 12/20 sand in 20# X-linked gel. CO after frac & released RBP @ 3590' & TOH. CO to 4801'. On 3/3/10, landed 2-7/8" 6.5# L-80 tbg @ 4717'. Ran pump & rods. Released workover rig on 3/4/10.

Spud Date: 5/26/09

Drilling Rig Release Date: 6/7/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <u>Mike Pippin</u>	TITLE <u>Petroleum Engineer - Agent</u>	DATE <u>3/9/10</u>
Type or print name <u>Mike Pippin</u>	E-mail address: <u>mike@pippinllc.com</u>	PHONE: <u>505-327-4573</u>
For State Use Only		
APPROVED BY: <u>David Gray</u>	TITLE <u>Field Supervisor</u>	DATE <u>3-15-10</u>
Conditions of Approval (if any):		