

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-37044

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
STALEY STATE

8. Well Number #5

9. OGRID Number 255333

10. Pool name or Wildcat: (96836)
Red Lake, Glorieta-Yeso NE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter H : 1650 feet from the NORTH line and 330 feet from the EAST line
Section 30 Township 17-S Range 28-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3595' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Payadd Workover ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/12/10: MIRUSU. Set 5-1/2" CBP @ 4275'. PT 5-1/2" csg to 4800 psi-OK. Perfed middle Yeso @ 3982', 83', 84', 86', 87', 4002', 03', 04', 06', 07', 08', 09', 10', 11', 12', 21', 22', 23', 24', 25', 26', 27', 53', 54', 68', 70', 72', 74', 75', 76', 77', 78', 79', 80', 81', 82', 4106', 07', 08', 09', 10', 11', 12', 13', 27', 28', 44', 45', 46', 49', 50', 63', 64', 73', 74', 91', 92', 93', 4205', 06', 07', 08', 10', 11', 12', 13', 14', 15', 16', 17', 18' w/1-0.42" spf. Total 71 holes. Treated perfs w/3500 gal 15% NEFE acid & 150 perf balls. Fraced w/79,793# Ottawa 16/30 & 53,793 16/30 siber prop sand in 20# X-linked gel.

Set 5-1/2" CBP @ 3962'. PT csg to 4000 psi for 30 min-OK. Perfed upper Yeso @ 3668', 69', 70', 81', 82', 83', 84', 88', 89', 3725', 26', 27', 28', 29', 30', 31', 32', 33', 34', 35', 36', 50', 51', 68', 69', 70', 94', 96', 97', 98', 99', 3800', 05', 06', 07', 08', 13', 14', 32', 33', 34', 41', 42', 43', 44', 45', 46', 65', 66', 71', 72', 73', 74', 91', 92', 3906', 07', 08', 18', 19', 20', 39', 40', 41', 42', 43' w/1-0.42" spf. Total 66 holes. Treated perfs w/4422 gal 15% NEFE acid & 140 perf balls. Fraced w/100,287# Ottawa 16/30 & 37,054# siber prop 16/30 sand in 20# X-linked gel.

CO after frac & drilled CBPs @ 3962' & 4275' & CO to 4729'. On 2/17/10, landed 2-7/8" 6.5# J-55 tbg @ 4622. Ran pump & rods & initiated pumping frac fluid. Released workover rig on 2/18/10.

Spud Date: 10/27/09

Drilling Rig Release Date: 11/9/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 3/8/10

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 3-15-10
Conditions of Approval (if any):