Fôim 3160-5 (August 2007)

(Instructions on page 2)

UNITED STATES

DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT** FORM APPROVED OMB No 1004-0137 Expires July 31, 2010

5. Lease Serial No. LC-058481

Do not use this t	IOTICES AND REPO form for proposals t Use Form 3160-3 (A	6. If Indian, Allottee or	тл Р.Б.СЕIVED MAR 1 0 2010		
SUBMIT IN TRIPLICATE – Other instructions on page 2.			7. If Unit of CA/Agree	ment, Name and/or No.	
1. Type of Well			0.37.11.27	NMOCD ARTESIA	
✓ Oil Well Gas Well Other				WLH G4S Unit #33	
Name of Operator EnerVest Operating, L.L.C.		9. API Well No. 30-015-37019	9. API Well No. 30-015-37019		
3a. Address 1001 Fannin, Suite 800 Houston, Tx 77002-6707		3b. Phone No. (include area code) 713-465-1514		10. Field and Pool or Exploratory Area Loco Hills; Qu-GB-SA	
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)			1 .	11. Country or Parish, State Eddy County, NM	
1980' FSL & 2380' FWL Unit K	Sec 11, T18S - R29E		Eddy Cour	ty, NM 	
12 CHEC	CK THE APPROPRIATE BO	DX(ES) TO INDICATE NATURE OF	NOTICE, REPORT OR OTHE	ER DATA	
TYPE OF SUBMISSION		ТҮРЕ С	OF ACTION		
✓ Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other Injection well	
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	✓ Temporarily Abandon✓ Water Disposal	completion	
determined that the site is ready for Enervest Operating, LLC permitted Order #R13128. Proposed Injection Well completion RU Wireline & run GR/CCL/CBL log Acidize using 5,000 gal 15% NEFE, Leave well SI overnight. RU flowbar RIH with plastic-coated 2-3/8" 4.7# RIH w/injection assembly and set perform step-rate injection tests. Prepare well for injection.	r final inspection.) this well as a producer and procedure: s. RIH w/3-1/8" select-fir scale inhibitor and ball seack equipment, install cholors and EUE J-55 tubing, 2-3/8 acker 50' above the top of	e csg guns and perforate 2667'-28 alers. Frac w/ approx. 18,000 gal ke, open to flowback tank. B' x 4-1/2" injection packer, 2-3/8" S the Grayburg #4 sand.	ete as an injector for the appoint of the appoint of 25# cross-linked get and SEF ATTAC	roved WLH Waterflood project, , 0.5" EHD). 30,000# of 16/30 Brady.	
SUBJECT TO LIKE APPROVAL BY STA 14. I hereby certify that the foregoing is to		3/18/10			
Shirley Galik		Title Sr. Regulate	orv Tech		
Signature Shurllis	Gaeik	Date 02/15/2010		ADDDOVED	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by Conditions of approval, if any, are attached that the applicant holds legal or equitable the entitle the applicant to conduct operations	itle to those rights in the subject thereon	ct lease which would Office	BUI	MAR 5 2010 Paris Valls REAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE	
Title 18 U.S.C. Section 1001 and Title 43 fictitious or fraudulent statements or representations.			Ilfully to make to any departmen	or agency of the United State Sany false,	

WLH G4S Unit 33 30-015-37019 EnerVest Operating March 2, 2010 Conditions of Approval

- 1. Install a casing-tubing annulus valve and a pressure gauge on the valve. Leave this annulus open to the gauge (detecting any casing, tubing, or packer leak). Subsequent to any repairs, record and report (one time) a casing and tubing pressure reading with the date of reading. Record casing and tubing pressure readings at least once a week. Report and correct any annular or tubing pressure above the permitted maximum.
- 2. Conduct a Mechanical Integrity Test of 500 psig for 30 minutes on the injection tbg/csg annulus of the well. Document the test on no more than a 1,000psig calibrated recorder chart, connect a reliable 1,000psig max with a six inch or larger face gauge in the recorder line as a real time visual monitor. Notify Paul R. Swartz at 575.234.5985 and/or 575.200.7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575.361.2822.
- 3. Surface disturbance beyond the existing pad must have prior approval.
- 4. Closed loop system required.
- 5. A minimum of a 2M BOP is required and must be tested prior to performing operations.
- 6. Subsequent sundry with step rate injection test, MIT, and wellbore schematic is required.
- 7. Submit a completion report within 30 days of completion.

CRW 030210