

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-36725
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name RDX 16
8. Well Number 6
9. OGRID Number 246289
10. Pool name or Wildcat Brushy Draw- Delaware East
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3097'

RECEIVED

MAR 16 2010

NMOC D ARTESIA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
RKI - Exploration & Production, LLC.

3. Address of Operator
3817 NW Expressway, Ste. 950, Oklahoma City, Okla. 73112

4. Well Location
Unit Letter I : 2260 feet from the South line and 990 feet from the East line
Section 16 Township 26S Range 30E NMPM County EDDY

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

RIG UP AND SPUD IN 8-22-2009, DRILLED 17-1/2" HOLE TO 484'. Ran 12 joints (490.34') of 13-3/8", 54.5#, J-55, STC Casing. Landed Casing With Shoe @ 484'. Float Collar @ 404.8.'

CEMENT W/SCHLUMBERGER AS FOLLOWS:

PUMP SPACER 22 BBLs OF WATER/GEL SPACER @ 4.6BPM W/150PSI.

LEAD: MIXED 200SXS, YIELD: 1.97, 70BBLs, 12.9PPG OF CLASS C +1 4%D20+.2%D46+2% S1+10.87GPS WATER @ 6.5BPM W/297PSI.

TAIL: MIXED 200SXS, YIELD: 1.34, 47BBLs, 14.8PPG OF CLASS C +1%S1+6.36GPS WATER @ 6.5BPM W/388PSI.

DISPLACED WITH 68 BBL OF FRESH WATER.

RETURNED 30BBLs OF CEMENT TO SURFACE.

DRILLED OUT CEMENT 22.5 HOURS AFTER CEMENT IN PLACE.

Spud Date: 8-22-09

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gene Simer TITLE Operations SUPERINTENDENT DATE 3-15-10

Type or print name Gene Simer

E-mail address: gsimer@rkixp.com

PHONE: 575.885.1313

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 3-18-10
Conditions of Approval (if any):