

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Oil Cons.
N.M. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

I Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mack Energy Corporation

3. Address and Telephone No.

P.O. Box 960, Artesia, NM 88211-0960

RECEIVED

JAN 29 2004

OCD-ARTESIA

(505)748-1288

4. Location of Well (Footage, Sec., T. R., M. or Survey Description)

330 FSL & 330 FEL, Sec. 19-T17S-R28E, P

5. Lease Designation and Serial No.

LC-028546A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Red Lake Sand Unit #15

9. API Well No.

30-015-01457

10. Field and Pool, or Exploratory Area

Red Lake; Queen-Grayburg-SA

11. County or Parish, State

Eddy, NM

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

Mack Energy Corporation proposes to plug and abandon well as follows:

1. Notify BLM 24 hours prior to starting plugging operations.
2. Set 100' plug from 1754-1654'. WOC and tag.
3. Circulate hole w/mud gel.
4. Perforate @ 496' squeeze 100' plug 50' above and below 8 5/8 casing. WOC and tag..
5. Perforate @ 245' squeeze 100' cement back to 145'
6. Perforate @ 60' circulate cement to surface.
7. Install dry hole marker.

**APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS ATTACHED**

APPROVED

JAN 27 2004

**LES BABYAK
PETROLEUM ENGINEER**

14. I hereby certify that the foregoing is true and correct

Signed Jerry W. Sheng Title Production Clerk Date 1/26/04

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any: _____