Submit 3 Copies to Appropriate

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office **OIL CONSERVATION DIVISION** DISTRICT I P.O. Box 1980, Hobbs NM 88240 WELL API NO. 2040 South Pacheco 30-015-01460 DISTRICT II 811 South First, Artesia, NM 88210 Santa Fe, New Mexico 87505 5. Indicate Type of Lease STATE 🛛 FEE \square DISTRICT III 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd, Aztec, NM 87410 B-4456 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS). 1. Type Of Well: RECEIVED OIL GAS \boxtimes Red Lake Sand Unit OTHER WEL JAN 2 2 7004 2. Name of Operator 8. Well No. Mack Energy Corporation OCD-ARTESIA 3. Address of Operator 9. Pool name or Wildcat P.O. Box 960, Artesia, NM 88211-0960 Red Lake; Queen-Grayburg-SA 4. Well Location Feet From The ____ South 1650 Feet From The _ 28E Range Township County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3539 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTERING CASING REMEDIAL WORK **TEMPORARILY ABANDON** CHANGE PLANS PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER. 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Mack Energy Corporation proposes to plug and abandon well as follows: 1. Notify OCD 24 hours prior to starting plugging operations. 2. Set 100' cement plug from 1650-1550'. WOC and tag. 3. Circulate hole with mud gel. 4. Perforate @ 498' squeeze 100' cement 50' above and below 8 5/8 casing. WOC and tag. 5. Perforate @ 220' squeeze 100' cement back to 120'. 6. Perforate @ 60' circulate cement to surface. - Both Osq. Strings-woc 24 HRS 745 7. Install dry hole marker.

(This space for State Use)	<u> </u>	83.	1. Od La D	1AN 2 8 2004
TYPE OR PRINT NAME		Jerry W. Sherrell		TELEPHONE NO.
/)	ation above is true and complete to the best of	f my knowledge and belief.	Production Clerk	DATE1/22/04

APPROVED BY-

STATE

MACK ENERGY CORPORATION RED LAKE SAND UNIT #14 SEC 19 T17S R28E 330 FSL 1650 FEL

'8 5/8"-28#

- 1. Notify OCD 24 hrs. prior to any work done.
- 2. Set 100' plug 1650'-1550' & tag.
- 3.Circ hole with mud gel.
- 4.Perf @ 498' squeeze 100' cmt plug 50' above & below 8 5/8" and tag.
- 5. Perf 220' squeeze 100' cmt plug 50' above & below back to 120'.
- 6. Perf @ 60' circ cmt to surface
- 7. Install Dry Hole Marker

8 5/8" 28# @448' c/w 50sx.



7"20# @ 1650" c/w 100sx

4 1/2" LINER SET FROM 1831' back to 1600' Plugged back 1650' w/CIBP Perf 1600-1610'.