OPERATOR'S COPY UNITEDSTATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORMAPPROVED OM B No 1004-0137 Expires: March 31, 2007

NOV 1 6 200 SUNDRY NOTICES AND REPORTS ON WELLS

BOP

5. Lease Serial No NM02862

Do not use this form for proposals to drill or to country proposals abandoned well. Use Form 3160-3 (APD) for sure COWID PRODUCTION	o re-enter an ich proposals.
SUBMIT IN TRIPLICATE - Other instructions on	2 MIN CALMIMOOD ARTERIA
1. Type of Well Z OilWell GasWell Other 2. Name of Operator BOPCO, L.P. 3a. Address 3b. PhoneNo	NMNM 71016X 8. Well Name and No Poker Lake Unit #301H 9. API Well No. 30-015-36924 10. Field and Pool, or Exploratory Area Nash Draw (Delaware/BS/Avalon Sand 11 County or Pansh, State Eddy County NM
TYPEOF SUBMISSION	TYPE OF ACTION
Acidize Deepen Notice of Intent Alter Casing X Fracture Tr X Subsequent Report Casing Repair New Const Change Plans Plug and A Convert to Injection Plug Back	Struction Recomplete X Other Initial Abandon Temporarily Abandon Completion
Attach the Bond under which the work will be performed or provide the Bond N following completion of the involved operations. If the operation results in a multiesting has been completed. Final Abandonment Notices shall be filed only after determined that the site is ready for final inspection.) BOPCO, L.P. respectfully wishes to report the initial comp 09/15/09: MIRU Lucky Well Service. 09/16/09: RIH w/ packer to isolate leak. 09/17/09: Set packer. 09/18/09: RU Basic Energy Services & test csg. to 8250 pclosed loop system site location as per NMOCD specifica 09/19/09: Drill out FC and 68' of hard cement to leave PE 09/20/09: Preparing to RIH and set CIBP. 09/21/09: No activity. 09/22/09: RIH w/ CIBP @ 11,822. 09/23/09: Perforated 11,1888-90', 11,523'-25' and 11,819 09/24/09: RU Stinger Wellhead Services & Mann Testing 09/25/09: RU Mann Testing Service to test connecting line.	psi (held okay). Roadrunner Environmental Co. cleaned up ations. BTD @ 11,822'. 9'-21'. g Service. Tested plug and RD Mann Testing Service.
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Sandra J. Belt ext. 149	Title Regulatory Clerk
Signature Sandra J. Belt THIS SPACE FOR FEDERAL	Date 11/03/2009 ACCEPTED FOR RECORD
INIS SPACE FOR FEDERAL	L OK STATE OFFICE USE TO TON NEUVIN
Approved by Conditions of approval, if any, are attached Approval of this notice does not war certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for a States any false, fictitious or fraudulent statements or representations as to any	any person knowingly and willfully o make to app department of the property of the United

Attachment to Form 3160-5 Sundry Notice Item 13 7/17/09

09/30/09

MIRU Schlumberger pumping service and coiled tubing.

10/01/09:

Stage #1: Frac perfs 11,188' - 11,190', 11,523' -11,525' & 11,819' - 11,821' w/ 2,486 gals 15% HCL, 193,615 gals YF125 Borate-xlinked gel w/ 279,138 lbs

16/30 Ottawa sand.

Stage #2: Frac perfs 10,852' - 10,853' w/ 3,696 gals 15% HCL, 111,174 gals YF

125 Borate-xlinked gel w/ 125,478 lbs 16/30 Ottawa sand.

Stage #3: Frac perfs 10,516', & 10,517' w/ 2,856 gals 15% HCL, 79,716 gals

YF125 Borate-xlinked gel w/ 120,305 lbs 16/30 Ottawa sand.

10/02/09:

Stage #4: Frac'd perf 10,180' w/ 3,402 gals 15% HCL, 65,814 gals YF125

Borate-xlinked gel w/67,353 lbs 16/30 Ottawa sand.

Stage #5: Frac'd perf 9,844' w/ 3,029 gals 15% HCL, 24,236 gals 25# Linear,

46,455 gals YF125 Borate-xlinked gel w/ 128,701 lbs 16/30 Ottawa sand.

Stage #6: Frac'd perf 9,508' w/ 3,469 gals 15% HCL, 12,304 gals 25# Linear,

55,670 gals YF125 Borate-xlinked gel w/ 127,996 lbs 16/30 Ottawa sand.

Stage #7: Frac'd perf 9,172' w/ 3,570 gals 15% HCL, 10,332 gals 25# Linear,

56,112 gals YF125 Borate-xlinked gel w/ 126,469 lbs 16/30 Ottawa sand.

10/03/09:

Stage #8: Frac'd perf 8,836' w/ 3,402 gals 15% HCL, 46,888 gals YF125 Borate-

xlinked gel w/ 123,171 lbs 16/30 Ottawa sand.

Stage #9: Frac'd perf 8,500' w/ 3,194 gals 15% HCL, 13,439 gals 25# Linear,

58,127 gals YF125 Borate-xlinked gel w/ 124,137 lbs 16/30 Ottawa sand.

Stage #10: Frac'd perf 8,164' w/ 3,146 gals 15% HCL, 11,962 gals 25# Linear,

58,098 gals YF125 Borate-xlinked gel w/ 123,934 lbs 16/30 Ottawa sand.

Stage #11: Frac'd perf 7,824' w/ 5,166 gals 15% HCL, 9,844 gals 25# Linear,

59,540 gals YF125 Borate-xlinked gel w/ 128,918 lbs 16/30 Ottawa sand.

POOH w/CT.

10/04/09:

Cleaning out sand plugs. Working on pulling coil tubing out of hole.

10/05/09:

POOH w/coil tubing. Left 2-7/8" OD motor head assembly, agitator, gas

separator, mud motor and 4.625" OD junk mill as fish.

10/06/09:

MIRU Lucky Well Service. Recovered 100% of fish.

10/07/09 thru 10/08/09:

Continue washing and drilling sand cleaning wellbore out.

10/09/09:

Cleaned out to PBTD of 11,822. Good show of oil.

10/10/09:

POOH w/work string. RBIN w/production installation.

10/11/09:

Tesco hung transformers and wired electrical equipment. Opened well down

flowline.

10/12/09:

Waiting on tests.

10/13/09:

All rental equipment released. Well producing.