

Submit Copy to Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
October 13, 2009

WELL API NO.  
30-015-37451

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
K-4168

7. Lease Name or Unit Agreement Name

Parkway 26 State Com

8. Well Number  
2H

9. OGRID Number  
14744

10. Pool name or Wildcat  
Turkey Track Bone Spring 60660

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter\_D : 660' feet from the North line and 330' feet from the West line  
Section 26 Township 19S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3341' GL

RECEIVED

APR 19 2010

NMOCD ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/02/10...MI & spud 17 1/2" hole. TD'd hole @ 350'. Ran 350' 13 3/8" 48 H40 ST&C csg. Cemented with 400 sks Class "C" with 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circ 96 sks to pit. WOC 18 hrs. At 8:15 am 01/04/10 tested Csg & annular to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

01/11/10..TD'ed 12 1/4" hole @ 3303'. Ran 3303' 9 5/8" 36/40# J55 LT&C Csg. Cemented with 700 sks BJ Lite "C" (50:50:10) with additives. Mixed @ 11.7 /g w/ 2.52 yd. Tail with 200 sks Class "C". Mixed @ 14.8 #/g w/ 1.34 yd. Plug down @ 8:45 am 01/10/10. Circ 165 sks to pit. WOC 18 hrs. At 2:45 am 01/11/10 tested BOPE and casing to 1500# for 30 minutes, held Ok. Drilled out with 8 3/4" bit.

Spud Date: 01/02/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jacqui Lathan TITLE Hobbs Regulatory DATE 01/13/10

Type or print name \_\_\_\_\_ E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 4-22-2010  
Conditions of Approval (if any):