

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W. Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-36499
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-827 & VO-5867
7. Lease Name or Unit Agreement Name Perdomo BMP State Com
8. Well Number 1H
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Surface	L	:	1650	feet from the	South	line and	660	feet from the	West	line
BHL	I	:	1650	feet from the	South	line and	330	feet from the	East	line
Section	24	Township	24S	Range	27E	NMPM	Eddy	County		

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3149'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Surface and Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/30/10 - Resumed drilling at 11:20 PM.

5/1/10 - TD 17-1/2" hole to 805'.

5/2/10 - Set 13-3/8" 48# H-40 ST&C casing at 805'. Cemented with 450 sx Class "C" + 0.125#/sx D130 + 3.76#/sx D20 + 94#/sx D903 + 1.88#/sx S1 + 0.188#/sx D46 (yld 1.97, wt 12.9). Tailed in with 200 sx Class "C" + 0.125#/sx D130 + 94#/sx D903 + 0.94#/sx S1 (yld 1.34, wt 14.8). Cement circulated to surface. Tested casing to 600 psi for 30 min, ending 540 psi. NOTE: NMOCD was notified via voicemail and no representative on location to witness cement job. WOC 20 hrs. Reduced hole to 12-1/4" and resumed drilling.

5/3/10 - TD 12-1/4" hole at 2:00 AM to 2286'. Set 9-5/8" 36# J-55 LT&C casing at 2286'. Notified Mike Bratcher-NMOCD of pending cement job but did not witness. Cemented with 550 sx 35:65:6 Poz "C" + 0.621#/sx D112 + 27.65#/sx D132 + 5.325#/sx D20 + 4.827#/sx D44 + 61.1#/sx D903 + 0.177#/sx D46 (yld 2.07, wt 12.6). Tailed in with 200 sx Class "C" + 94#/sx D903 + 0.1% D13 (yld 1.33, wt 14.8). Cement circulated to surface. Tested casing to 1200 psi for 30 min - no pressure loss. WOC 48 hrs. Reduced hole to 8-3/4" and resumed drilling.

Spud Date:

8/1/08

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE May 19, 2010

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 6-1-2010

Conditions of Approval (if any):