

RECEIVED

OCT 3 9 35 AM '94  
CALIF. AREA

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM OIL & GAS COMMISSION  
Drawer DD  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Stevens & Tull, Inc.

3. Address and Telephone No.

P. O. Box 11005, Midland, Texas 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL  
Sec. 1, T21S, R21E

5. Lease Designation and Serial No.  
NM 27451

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Nasser Federal #1

9. API Well No.

30-015-27865

10. Field and Pool, or Exploratory Area

Little Box Canyon-Morrow

11. County or Parish, State

Eddy, New Mexico

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 9/14/94 - Isolate Morrow perforations from 7862' - 7868' using a 1.87 Blanking Plug on Slickline. POH with tubing and perforate Canyon Sand from 7148' - 7156' 4 SPF total 32 holes.
- 9/15/94 - Acidize Canyon perfs. with 1000 gallons NEHCL 15% Swab and flow back acid. Test thru sales line at 30 MCF/d.
- 9/16/94 - Run on/off tool and latch onto profile nipple and pull out blanking plus across Morrow perforations.
- 9/20/94 - Producing Morrow up tubing and Canyon up casing - Evaluating potential Frac.

1994

JV

14. I hereby certify that the foregoing is true and correct

Signed

*Michael J. [Signature]*

Title

Engineer

Date

9/29/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date