ATS-10-507

OMB No 1004-0137 Expires March 31, 2007 10-686

Lease Serial No.

If Indian, Allotee or Tribe Name

LL- 068284

OCD-ARTESIA NMOCD ARTESIAM

Form 3160-3 (April 2004)

> UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

				i e	
la Type of work	REENT	ER		7 If Unit or CA Agreement	, Name and No
lb Type of Well Oil Well	Gas Well Other	✓ Single Zône	Multiple Zone	8 Lease Name and Well N North Indian Flats	, ,
2 Name of Operator BOPCO, L. P.	/2	60737		9 API Well No 30-015-	-37903
3a Address P. O. Box 2760 Midland, TX 79702		3b Phone.No (include frea c 432-683-2277	rode)	10 Field and Pool, or Explor -Undesignated (Dela	. ,,
4 Location of Well (Report location clean At surface NESW, U At proposed prod zone	*	ny State requirements *) 2, Lat N32.463931, Long W	104.033550	11 Sec, T R M or Blk and Sec 24, T21S, R28E	Survey or Area
14 Distance in miles and direction from ne 6 miles east of Carlabad, NM	earest town or post office*		***************************************	12 County or Parish Eddy County	13 State NM
Distance from proposed* location to nearest property or lease line, ft (Also to nearest drig unit line, if any)	660'	16 No of acres in lease	17 Spacin	g Unit dedicated to this well	•
18 Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft	1320'	19 · Proposed Depth 3400'		BIA Bond No on file	
Flevations (Show whether DF, KDB, 3247' GL	RT, GL, etc)	22 Approximate date work will start* 10/31/2010		23 Estimated duration 8 days	

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No 1, shall be attached to this form

- 1 Well plat certified by a registered surveyor
- 2 A Drilling Plan
- 3 A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office)
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above)
- Operator certification
- Such other site specific information and/or plans as may be required by the

Signature	Vilders	Name (Printed/Typed) Annette Childers	H-19-2010		
Title Regulatory	Clerk				
Approved by (Signature)	/s/ Don Peterson	Name (Printed/Typed) ISI Don Peterson	DateMAY 2 0 2000		
Title FIELD MANAGER Application approval does not warrant or certify that the applicant holds		Office CARLSBAD FIELD OFFICE dis legal or equitable title to those rights in the subject lease which would entitle the applicant to			
14					

conduct operations thereon.

Conditions of approval, if any, are attached

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*(Instructions on page 2)

Capitan Controlled Water Basin

SEE ATTACHED FOR CONDITIONS OF APPROVAL

APPROVAL SUBJECT TO **GENERAL REQUIREMENTS** AND SPECIAL STIPULATIONS **ATTACHED**

DISTRICT I 1625 N French Dr., Hobbs, NM 88240 DISTRICT II

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised October 15, 2009

Submit one copy to appropriate

District Office

1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION

1220 South St. Francis Dr. Santa Fe, New Mexico 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-015-37903	33735	TNNAN FLATSON Name Undesignated (Delaware)	ELAWARE
Property Code 38104		roperty Name FLATS "24" FEDERAL	Well Number
OGRID No. 260737		perator Name PCO, L.P.	Elevation 3247'

Surface Location


UL or lot No.	Section	Township	Range	Lot ldn	Feet from the	North/South line	Feet from the	East/West line	County
1	24	21 S	28 E		1980	SOUTH	660	EAST	EDDY


Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
									,
Dedicated Acres	Joint o	r Infill Co	nsolidation (Code Ore	der No.				
40	N								

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

 OR A NON-STAN	DARD UNIT HAS BEI	EN APPROVED BY TH	E DIVISION
			OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract unth an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Signature Gary E. Gerhard Printed Name
· — — — — — — — — — — — — — — — — — — —	SURFACE LOCATION Lat - N 32°27'50.15" Long - W 104'02'00.78" NMSPCE - N 532638.848 £ 633796.184 (NAD-83)	3250.7' 3251 3'	SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison and that the same is true and correct to the best of my belief Date Surveyed MEX Signature &






NORTH INDIAN FLATS "24" FEDERAL #4
Located 1980' FSL and 660' FEL
Section 24, Township 21 South, Range 28 East,
N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786 1120 N. West County Rd. Hobbs, New Mexico 88241 (575) 393-7316 - Office (575) 392-2206 - Fax basinsurveys.com

	W.O. Number: JMS 22328	
	Survey Date: 02-04-2010	١,
I	Scale: 1" = 2000'	ľ
I	Date: 02-11-2010	

BOPCO, L.P.




NORTH INDIAN FLATS "24" FEDERAL #4 Located 1980' FSL and 660' FEL Section 24, Township 21 South, Range 28 East, N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786 1120 N. West County Rd. Hobbs, New Mexico 88241 (575) 393-7316 - Office (575) 392-2206 - Fax basinsurveys.com

W.O. Number: JMS 22328	-
Survey Date: 02-04-2010	3
Scale: 1" = 2 Miles	Ŋ
Date: 02-11-2010	

BOPCO, L.P.



NORTH INDIAN FLATS "24" FEDERAL #4
Located 1980' FSL and 660' FEL
Section 24, Township 21 South, Range 28 East,
N.M.P.M., Eddy County, New Mexico.



P O Box 1786 1120 N West County Rd Hobbs, New Mexico 88241 (575) 393-7316 - Office (575) 392-2206 - Fox basinsurveys com W O Number JMS 22328

Scale 1 = 2000

YELLOW TINT - USA LAND
BLUE TINT - STATE LAND
NATURAL COLOR - FEE LAND

BOPCO, L.P.


North Indian Flats 24 Fed #4 Exhibit "A"



			AND THE REAL PROPERTY.	N/ V/ - 1/10/24 - 1	N 63 - 2135 61 - 3	33 13, 12W 2	SALAS MAISTE A	11.55 - 7.12 E
21.05 47.07 17.00 17.00 1	<i>1</i> ∕2*	2713 212718 I	M	wbourne 2016 115412 2 800 E		145	345 O ere	rodeo Frop.
Energex Co	10.73% va	1016, 115409 130016, 115409 130011 (HNG)		, , , , ,	3 x 8000 40	يعوى والمعواليف	Pronjoin	(Co.)
100 10 10 9	a* 11	2000			g, 25 (5 6)	1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1	1 1/1515 Digs	3100 Fed
1900 के निकासित 51	Tates Fet etal Cret 71 2016 Eco	CHANGE COMITY	GA P	Harris Dome	, , ,	www.		
1 1 4 4 5 15 A	\$ 100 00 9	7300 (HMG)	HBP 01	Can Brown	ا چه چور	The state of the s	Meooco 13635	
Mate (Page) Mate (Page)			With sec	Meadro	, L.O.	Harris eggico)	Fed H Wasso	Sre skille registry
A A A	Yoje	s Pet ets: 1 - 2016	30 40 -₹			, 4 .	Meadon 13633 Meado	
NGK Fa Expariantal St. (OXY)	11	(800 <u>≈</u>		Fren Enginger Tuggeb 0/44-21 56	J/A 100	-Birγ Harris Fale 0		1
(ORY- Pranghorn-St)	Nodel E. G	055 (137) 0000 7 2 007 25	Scal Calling I	L. Wesse	Mandoo	وه آه و يد	Mereowine 02950	
stote		·	78 6650		Mandeo Horris-Fed		\$ Entinge"	
Buss Ent. Buss Ent. SR Buss, Thru Line Inc. (14)	Signer dyan Dir 12 1 - 5 8 c 11 0 1 0 6 6		5 d h 3 ec	S R Boss,	Bass (at	. Charles and a second		dson Oii
Thrubing 061239 6 3-50 McCept 1 HBF 063543)	THE WLINE OL . 1940. 762273	Thru Line Inc. elia 1 065284 1857	0505 181 6411	Richardson Oil		58 (2)
Big Eddy Unit TUSASA Richardson Oil Richardson Oil		l ;	7337 F 77	1	89	} 1	:	-George 16418
Richardson Oil Nichardson Oil	P charasen Oil	27,500	T 34 T	7		B Bess Ent	,	3
gesser 4 066645	8 1 6'(t	. 267 65 € 2 6			Crargant Baps	Bichardson (ii) 0505 31, 38	ĺ	
	liles."	PR Boss (Big Eddy Unit)	જ યહે		67944 F143	Picker Friday		
So Arrive Ted 5 089719	letter .			•	Ry Eddy	Garden Fed		
Richardson Oil Richardson Oil 1 1 61621 0 1 89 T	Rizhard Z - 1	w1 1 7)		* E A P . 25 7 ;	l Bass Enf	515a	chi de stata	
063516 1 366619	367	4.5	#8.7 € #35 *	.67	0 54 9 Gast	tent 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Turned etal Viel	(Bettie Blos)
1	1	Hanetss (ene → 11)535	יר וגיע	# 84 1, A101	104	i All	sic Ch Oper	Brea Cru Oper
9015 Ent , SR Bass,	F 570 Factor 57 - 1	3	יז א ס	18	Golden-Fed	7	Primas Ener Big Eddy Ur	(1.67,19.29)
SE CHE COLD Thru Line Inc., exp.	7 6' 21 068358	1		PonAmer S g E des	Richardson Oil 2 + 60 il	Pichardsan Oil Tillen Tillen	Big Eddy UT - 127	691 (13 K%)
Rehard 18 g lany		}	DO SO STEREGYPE	3 9 8 9 8 9 8 9	# 60 01318	1	F .	1800
416 CC 1 2 3			referes. High	Bg Eddy	,	1 .†s	510	1 2 Sur 1 2
8ass Ent 641719	E.R. Bass Fraulineine, et i	F cho distroit	102			Ĺ		BESTIEL OS ETOL SON OUT BESTIE OF OUT
	064 184	1 /43/45			well North	2 1 64 (2)	*310	1 HBU 19318 an
76 ⊅ 18міі,		1		Indian Flat	s 24 Fed #4	# hd	I REPORT	i_ (⊗"
 23	2	4	327 1	· · · · · · · · · · · · · · · · · · ·	89 5 49 2) 0	1 (33)	Berlis Bros Pos
ALIE,K	Thru time Inc. eta.	They Line Inc Otol	Richar 0-1	disan ee gasii	Ficharaten Oil	Fighardsas Orl	Thrulis	seine etal
" TigEddy"	,,,,,	1 ива	Te. 7 2434	~ Dip 34.**	E525 4911	34198 H8J	406	55 (1) 39 (6
νς υς	Ĺ			⊕**		153 Politic	, ,	1.11
Bass Ent. 70	flass Ent	⊅ ™	SR Boss	<u></u>	€ con Out	Richardson Oil	Sicord	Pichardson (*)
T411)		6 4 Mai	FREN Line loc , etc	They Line Inc., etal.	ивр сея44	6-1-63(7) 1 069241	1 I	6 1 11(2)
Boss Ent.				наг	i	Heu	H B P	- Fu
26	2	5	wu #	30	2			8
ال المحرية الم	T/A XX	Thru Line Inc., eta- 3 8 8 7 8 4 4 HBP				3 P	Richard	3 P
la aut	Ry Feldy"	l """	\$ P.R. Bais Elg Esty (1311 \$74) 27	· /1	069	144	253	14
Big Eddy'	ι <u>.</u>				Ü		u	5
PR Bass 4 8ass 3.25544 59 067144	⊕'	:	S R Boss	R chordson Oil	4 2 P II Boss		 	Richardson Oil
163796 - 0	Shel Beroay	Bass Ent F 5332	Fitting Eige Inc. plus 06 25 73 MBP 148 2 77 7 7 -	48°	By Eddy W	HBP	Richardson 01' 21 60 21 60 811033 03205 HBU 1 HBU	
25 O 160 (619)	1 C 4 C 5 9		943¥ _{+ −}	•	819 Eddy er 00 1307 5 014 3 4-75		HEW I HEW	; i
Ord 35 TO 1000	3	6 Sprint Tark		3:	Tipledine in 3	2	3	5
PAT GE BASSENT TO BE BASSENT T	(*, (\$ ³)	CESS.	no f		reledyne Ind 3	1	Richo 8 i	rdson 0() (\$1(2) (\$179
			Piata"a re − r	nige yn e	a nower			BU. The As
`~ ₁₀ €3	"B.9 £			3	<u> </u>	5		5
· " A · " " · S · S · S · S · S · S · S · S · S ·		and the state of t	EN Park	Acres (All Property of		3		(*a)/20- (*


North Indian Flats 24 Fed #4 Exhibit "B"





North Indian Flats 24 Fed #4 Exhibit "C"






NORTH INDIAN FLATS "24" FEDERAL #4 Located 1980' FSL and 660' FEL Section 24, Township 21 South, Range 28 East, N.M.P.M., Eddy County, New Mexico.

North Indian Flats 24 Fed #4 Exhibit "E"





NORTH INDIAN FIATS "21" FEDERAL #4 Located 1980' FSL and 660' FEL Section 21, Township 21 South, Range 28 East, N.M.P.M., Eddy County, New Mexico. Surface casing to be set into the Rustler below all fresh water sands.



Production casing will be cemented using Schlumberger TXI LiteWate plus additives with TOC @_2308*.

Drilling procedure, BOP diagram, anticipated tops and surface plans attached.

This well is located outside the Secretary's Potash area and outside the R-111 Potash area. There are potash leases within 5 miles of the location. (4 miles southeast)

BOPCO, L.P., at P. O. Box 2760, Midland, TX, 79702 is a division office of BOPCO, L.P., 201 Main Street, Ft. Worth, TX 76102, Bond No. COB000050 (Nationwide).

EIGHT POINT DRILLING PROGRAM BOPCO, L.P.

NAME OF WELL: North Indian Flats 24 Federal #4

LEGAL DESCRIPTION - SURFACE: 1980' FSL & 660' FEL, Section 24, T21S, R28E, Eddy County, New Mexico.

POINT 1: ESTIMATED FORMATION TOPS

(See No. 2 Below)

POINT 2: WATER, OIL, GAS AND/OR MINERAL BEARING FORMATIONS

Anticipated Formation Tops. KB 3258' GL 3247'

	ESTIMATED	ESTIMATED	
FORMATION	TOP FROM KB	SUBSEA TOP	BEARING
T/Rustler	Surface'		Barren
B/Rustler	398'	+ 2,850'	Barren
T/Salt	468'	+ 2,790'	Barren
B/Salt	2,308'	+ 950'	Barren
T/Delaware Mtn Grp	2,694'	+ 564'	Oil/Gas
Clean Carb above R. Sd	2,813'	+ 445'	Oil/Gas
T/Ramsey Sand	2,841'	+ 417'	Oil/Gas
TD	3.400'	- 142'	Oil/Gas

POINT 3: CASING PROGRAM

TYPE	HOLE SIZE	<u>INTERVALS</u>	<u>PURPOSE</u>	CONDITION
14"	20"	0' - 40'	Conductor	Contractor Discretion
8 5/8", 32#, J-55, 8rd STC	12-1/4"	0' - 458'	Surface	New
5-1/2", 15.5#, J-55, 8rd STC	7-7/8"	0' - 3,400'	Production	New

CASING DESIGN SAFETY FACTORS:

TYPE	TENSION	<u>COLLAPSE</u>	<u>BURST</u>
8-5/8", 32#, J-55, 8rd STC	28.77	6.62	6.66
5-1/2", 15.5#, J-55, 8rd STC	4.66	1.76	1.42

DESIGN CRITERIA AND CASING LOADING ASSUMPTIONS:

SURFACE CASING

Tension A 1.6 design factor utilizing the effects of buoyancy (9.2 ppg).

Collapse A 1.0 design factor with full internal evacuation and a collapse force equal to the

mud gradient in which the casing will be run (0.48 psi/ft). The effects of axial load

on collapse will be considered.

DESIGN CRITERIA AND CASING LOADING ASSUMPTIONS: - con't...

Burst

A 1.3 design factor with a surface pressure equal to the fracture gradient at setting depth less a gas gradient to the surface. Internal burst force at the shoe will be fracture pressure a that depth. Backup pressure will be formation pore pressure. In all cases a conservative fracture pressure will be used such that it represents the upper limit of potential fracture resistance up to a 1.0 psi/ft gradient. The effects of tension on burst will not be utilized.

PRODUCTION CASING

Tension A 1.6 design factor utilizing the effects of buoyancy (10.0 ppg).

Collapse A 1.0 design factor with full internal evacuation and a collapse force equal to the

mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load

on collapse will be considered.

Burst A 1.25 design factor with anticipated maximum tubing pressure (3000 psig) on

top of the maximum anticipated packer fluid gradient. Backup on production strings will be formation pore pressure (0.43 psi/ft). The effects of tension on

burst will not be utilized

POINT 4: PRESSURE CONTROL EQUIPMENT (SEE ATTACHED DIAGRAM)

A BOP equivalent to Diagram 1 will be nippled up on the surface casing head. The BOP stack, blind and pipe rams, chokes, kill line, Upper and lower Kelly valves, inside BOP, choke manifold when rigged up on the surface casing will be tested to 2000 psig (working pressure of BOPE) by independent tester (must use test plug). 8-5/8" casing will be tested to 1500 psig.

These tests will be preformed.

- a) When initially installed
- b) Whenever any seal subject to test pressure is broken
- c) Following related repairs
- d) At 30 day intervals

A function test to insure that the preventers are operating correctly will be performed on each trip. See the attached Diagram 1 for the minimum criteria for the choke manifold.

POINT 5: MUD PROGRAM

DEPTH	MUD TYPE	WEIGHT_	FV	PV	YP	FL	<u>Ph .</u>
0' - 458'	FW	8.5 - 9.2	45-35	NC	NC	NC	9.5
458' - 3,400'	BW	10.0 - 10.3	28-30	NC	NC	NC	9.5

POINT 6: TECHNICAL STAGES OF OPERATION

A) TESTING

No drill stem tests are planned

POINT 6: TECHNICAL STAGES OF OPERATION - con't ...

B) LOGGING

See CoA

Run #1:

Pex (GR-CNL/LDT) @ TD. GR/CNL to surface.

C) CORING

No cores are anticipated.

D) CEMENT

INTERVAL	AMOUNT SX	FT OF FILL	TYPE	GALS/SX	<u>PPG</u>	FT ³ /SX
SURFACE Lead 0'-458' (100% excess) (Circulated to surface)	320	443	Class-C + 2% CaCl	6 39	14 8	1 35
PRODUCTION: Tail 2,308'-3,400' (100% excess)	270	1098	TXI LiteWate + 0.2% NaCl + 0.3% D167 + 0 15% DO65 + 0 125 pps D130 + 3 pps DO42	7 04	13 0	1 41

COA

E) DIRECTIONAL DRILLING

No directional services anticipated

POINT 7: ANTICIPATED RESERVOIR CONDITIONS

Normal pressures are anticipated throughout the Delaware section. A BHP of 1472 psi (max) or MWE of 8 33 ppg is expected. The Ramsey production does contain H₂S A H₂S contingency plan covering all of Sec 24 & 25 will be submitted separately.

POINT 8: OTHER PERTINENT INFORMATION

A) Auxiliary Equipment

Upper and lower kelly cocks. Full opening stab in valve on the rig floor.

B) Anticipated Starting Date

Spud date is 10/31/2010.

8 days drilling operations


7 days completion operations

GEG/mac

North Indian Flats 24 Fed #4 Exhibit "D"




BOPCO, L.P RIG LAYOUT SCHEMATIC INCLUSIVE OF CLOSED-LOOP DESIGN PLAN CAPSTAR TYPE RIG



BOPCO, **L. P.** 2000 PSI WP

TO MUD/GAS SEPARATOR AND/OR PIT



THE FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

- A. One double gate Blowout preventer with lower pipe rams and upper blind rams, all hydraulically controlled. controlled.
- B Opening on preventers between rams to be flanged, studded or clamped and at least two inches in diameter.
- C. All connections from operating manifold to preventers to be all steel hose or tube a mininum of one inch in diameter.
- D. The available closing pressure shall be at least 15% in excess of that required with suffficient volume to operate (close, open, and re-close) the preventers.
- E. All connections to and from preventers to have a pressure rating equivalent to that of the BOPs.
- F. Manual controls to be installed before drilling cement plug.
- G. Valve to control flow through drill pipe to be located on rig floor.
- H. Chokes must be adjustable. Choke spool may be used between rams.

DIAGRAM 1

➤ TO STEEL MUD TANKS

→ BLEED LINE TO STEEL PIT (NOT CONNECTED TO BUFFER TANK

MULTI-POINT SURFACE USE PLAN

NAME OF WELL: North Indian Flats 24 Federal #4

LEGAL DESCRIPTION - SURFACE: 1980' FSL & 660' FEL, Section 24, T21S, R28E, Eddy County, New Mexico.

POINT 1: EXISTING ROADS

A) Proposed Well Site Location

See Exhibit "A".

B) Existing Roads

From mile marker 42 on Highway 62-180, go west 0.6 miles to lease road. On lease road to south 4.4 miles thence east 2.0 miles to lease road, on lease road go north 2.9 miles to proposed lease road.

C) Existing Road Maintenance or Improve Plan

See Exhibit "B"

POINT 2: NEW PLANNED ACCESS ROUTE

A) Route Location

See Exhibit "B". The new road will be 12' wide and approximately 2521.6' long from existing lease road. The road will be constructed of watered and 6" of compacted caliche.

B) Width

12' Wide.

C) Maximum Grade

Not Applicable.

D) Turnouts

As required by BLM stipulations.

E) Culverts, Cattle Guards, and Surfacing Equipment

None.

POINT 3: LOCATION OF EXISTING WELLS

Exhibit "A" indicates existing wells within the surrounding area.

POINT 4: LOCATION OF EXSITING OR PROPOSED FACILITIES

A) Existing facilities are located within one mile which are owned and controlled by lessee/operator:

Closest Oil/Gas production facilities are located at the Big Eddy #74 well site. The North Indian Flats 24 Federal #4 is located approximately 2640' northeast of the Big Eddy #74. (See Exhibit "A")

B) New Facilities in the Event of Production:

Additional production facilities will be added to the Big Eddy #74 (Section 25, T21S-R28E, NWNE) and will be used via 2-7/8" flow lines laid on top of ground. A new flow line consisting of 2-7/8" steel pipe will be laid within 50' of the centerline of the access road and existing roads which have previously been arch cleared. (See exhibit "E") Initially no power lines will be installed. A rental electric generator will be set to power pumping unit.

C) Rehabilitation of Disturbed Areas Unnecessary for Production:

Following the construction of production facilities, those access areas required for continued production will be graded to provide drainage and minimize erosion. The areas necessary for use will be graded to blend in the surrounding topography — See Point 10

POINT 5: LOCATION AND TYPE OF WATER SUPPLY

A) Location and Type of Water Supply

Fresh water will be hauled from the City of Carlsbad or piped from the IMC Booster Station water well located 5.2 miles east of Carlsbad. Brine water will be hauled from I & W Brine Water Station 0.75 miles southeast of Carlsbad.

B) Water Transportation System

Water hauled to the location will be over the existing and proposed roads or transported via temporary poly-line from the fresh water source.

POINT 6: SOURCE OF CONSTRUCTION MATERIALS

A) Materials-

Caliche source located in Sec. 5, T21S, R29E

B) Land Ownership

Federally Owned.

C) Materials Foreign to the Site

Caliche will be hauled from the nearest BLM approved caliche pit

POINT 6: SOURCE OF CONSTRUCTION MATERIALS - con't...

D) Access Roads

2521.6' of new access roads are required. See Exhibit "B".

POINT 7: METHODS FOR HANDLING WASTE MATERIAL

A) Cuttings – Closed Loop System

Cuttings will be contained in the steel pits and will be hauled to an approved disposal facility.

B) Drilling Fluids – Closed Loop System

Drilling fluids will be contained in the steel pits, frac tanks, and will be disposed of at licensed disposal facilities.

C) Produced Fluids

Water production will be contained in the steel pits.

Hydrocarbon fluid or other fluids that may be produced during testing will be retained in test tanks.

D) Sewage

Current laws and regulations pertaining to the disposal of human waste will be complied with

E) Garbage

Portable containers will be utilized for garbage disposal during the drilling of this well.

F) Cleanup of Well Site

Upon release of the drilling rig, the surface of the drilling pad will be graded to accommodate a completion rig if electric log analysis indicate potential productive zones Reasonable cleanup will be performed prior to the final restoration of the site.

POINT 8: ANCILLARY FACILITIES

None required.

POINT 9: WELL SITE LAYOUT

A) Rig Orientation and Layout

Exhibit "D" shows the dimensions of the well pad and closed loop system, and the location of major rig components. Only minor leveling of the well site will be required. No significant cuts or fills will be necessary.

B) Locations of closed loop system and access road

See Exhibit "D" & Exhibit "C".

C) Lining of the Pits

No reserve pit. Closed loop system.

POINT 10: PLANS FOR RESTORATION OF THE SURFACE

A) Reserve Pit Cleanup - Not applicable (see Point 9C above).

The pits will be fenced immediately after construction and shall be maintained until they are backfilled. Previous to backfill operations, any hydrocarbon material on the pits' surfaces shall be removed. The fluids and solids contained in the pits shall be backfilled with soil excavated from the site and soil adjacent to the reserve pits. The restored surface of the pits shall be contoured to prevent impoundment of surface water flow. Water-bars will be constructed as needed to prevent excessive erosion. Topsoil, as available, shall be placed over the restored surface in a uniform layer. The area will be seeded according to the Bureau of Land Management stipulations during the appropriate season following restoration.

B) Restoration Plans - Production Developed

In addition, those areas not required for production will be graded to blend with the surrounding topography. Topsoil, as available, will be placed upon those areas and seeded. The portion of the site required for production will be graded to minimize erosion and provide access during inclement conditions. Following depletion and abandonment of the site, restoration procedures will be those that follow under Item C.

C) Restoration Plans - No Production Developed

With no production developed, the entire surface disturbed by construction of the well site will be restored. The site will be contoured to blend with the surrounding topography and provide drainage of surface water. The topsoil, as available, shall be replaced in a uniform layer and seeded according to the Bureau of Land Management's stipulations.

D) Rehabilitation's Timetable

Upon completion of drilling operations, the initial cleanup of the site will be performed as soon as weather and site conditions allow economic execution of the work.

POINT 11: OTHER INFORMATION

A) Terrain

Relatively flat.

B) Soil

Caliche and sand.

C) Vegetation

Sparse, primarily grasses and mesquite with very little grass.

D) Surface Use

Primarily grazing.

E) Surface Water

There are no ponds, lakes, streams or rivers within several miles of the wellsite.

F) Water Wells

There are no water wells located within one mile of the proposed well site.

G) Residences and Buildings

None in the immediate vicinity.

H) Historical Sites

None observed.

I) Archeological Resources

An archeological survey has been performed for this area and will be submitted to the Bureau of Land Management. Any location or construction conflicts will be resolved before construction begins.

J) Surface Ownership

The well site is on federal owned land.

- K) Well signs will be posted at the drilling site.
- L) Open Pits None used. Closed loop system.

POINT 12: OPERATOR'S FIELD REPRESENTATIVE

(Field personnel responsible for compliance with development plan for surface use).

DRILLING W. R. Dannels Box 2760 Midland, Texas 79702 (432) 683-2277 PRODUCTION Dean Clemmer 3104 East Green Street Carlsbad, New Mexico 88220 (575) 887-7329

Carlos Cruz Box 2760 Midland, Texas 79702 (432) 683-2277

OPERATOR CERTIFICATION

4/13/10

I hereby certify that I, or persons under my direct supervision have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in the plan are, to the best of my knowledge, true and correct, and that the work associated with operations proposed herein will be performed by BOPCO, L.P. and it's contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Date

Gary E. Gerhard

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME: LEASE NO.: LC-068284

WELL NAME & NO.: North Indian Flats 24 Federal #4

SURFACE HOLE FOOTAGE: 1980' FSL & 660' FEL

BOTTOM HOLE FOOTAGE SAME

LOCATION: Section 24, T. 21 S., R 28 E., NMPM

COUNTY: Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

General Provisions
Permit Expiration
Archaeology, Paleontology, and Historical Sites
Noxious Weeds
Special Requirements
Lesser Prairie-Chicken Timing Stipulations
Ground-level Abandoned Well Marker
Avoidance of a Wildlife Water
⊠ Construction
Notification
V-Door Direction – Not stipulated
Topsoil
Closed Loop System
Federal Mineral Material Pits
Well Pads
Roads
Road Section Diagram
☑ Drilling
Medium Cave/Karst
Logging Requirements
Onshore Order 6 – H2S Requirements
⊠ Production (Post Drilling)
Well Structures & Facilities
Pipelines – Surface Steel pipeline requested
Electric Lines
☐ Interim Reclamation
☐ Final Abandonment & Reclamation

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Ground-level Abandoned Well Marker to avoid raptor perching: The well marker will be approximately 2 inches above ground level and contain the following information: operator name, lease name, and well number and location, including unit letter, section, township, and range. The previous listed information will be welded, stamped, or otherwise permanently engraved into the metal of the marker.

Practice avoidance of habitat water source during construction and drilling activities. The BLM requires that activities within 200 meters from an artificial wildlife water source be limited and short term in nature.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

For more installation details, contact the Carlsbad Field Office at 575-234-5972.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5972 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. V-DOOR DIRECTION: Not stipulated:

C. TOPSOIL

The operator shall stockpile the topsoil in a low profile manner in order to prevent wind/water erosion of the topsoil. The topsoil to be stripped is approximately 10 inches in depth. The topsoil will be used for interim and final reclamation.

Operator shall separate top-soil from any other materials placed on location as a result of "flipping" surface materials to expose and/or extract caliche from underneath the well-pad location.

D. CLOSED LOOP SYSTEM.

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

E. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

F. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed thirty (30) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning


Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on the uphill side of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:




Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope:
$$\frac{400'}{4\%}$$
 + 100' = 200' lead-off ditch interval

Culvert Installations

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

Fence Requirement

Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

- center line of roadway shouldertornout 10'

25° no between the transfer of the strong of the **Typical Turnout Plan Embankment Section** 03 - 05 ft/ft earth surface .02 - .04 h/h .02 - .03 h/h aggregate surface the bottom of the ditch **Side Hill Section** travel surface travel surface 4 (slope 2 - 4%) (slope 2 - 4%)

Figure 1 - Cross Sections and Plans For Typical Road Sections

Typical Inslope Section

Typical Outsloped Section

VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822

- 1. A Hydrogen Sulfide (H2S) Drilling Plan should be activated 500 feet prior to drilling into the Delaware formation. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.
- 2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
- 3. The record of the drilling rate along with the CAL/GR/N well log run from TD to surface will be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

B. CASING

Changes to the approved APD casing and cement program require submitting a sundry and receiving approval prior to work. Failure to obtain approval prior to work will result in an Incident of Non-Compliance being issued.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Medium Cave/Karst Possible lost circulation in the Delaware and Bone Spring Formation.

- 1. The 8-5/8 inch surface casing shall be set at approximately 458 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. If salt is encountered the casing must be set 25 feet above the salt.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with a surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
- 2. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement to surface due to cave/karst. If cement does not circulate, contact the appropriate BLM office. Additional cement will be required to bring the cement to surface.
- 3. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.

- 2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M)** psi.
- 3. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. Casing cut-off and BOP installation will not be initiated until the cement has had a minimum of 8 hours setup time for a water basin. The casing shall remain stationary and under pressure for at least eight hours after the operator places the cement. In the potash area, the minimum time is 12 hours and the casing shall remain stationary and under pressure during this time period. Casing shall be under pressure if the operator uses some acceptable means of holding pressure or if the operator employs one or more float valves to hold the cement in place. Testing the BOP/BOPE against a plug can commence after meeting the above conditions plus the BOP installation time.
 - b. The tests shall be done by an independent service company utilizing a test plug.
 - c. The results of the test shall be reported to the appropriate BLM office.
 - d. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

CRW 051910

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Containment Structures

The containment structure shall be constructed to hold the capacity of the entire contents of the largest tank, plus 24 hour production, unless more stringent protective requirements are deemed necessary by the Authorized Officer.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color Shale Green, Munsell Soil Color Chart # 5Y 4/2

B. PIPELINES – Surface Steel, 3 /78"

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the

release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

- 4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:
- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-of-way width of feet.
7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.
8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky of duney areas, the pipeline will be "snaked" around hummocks and dunes rather then suspended across these features.
9. The pipeline shall be buried with a minimum of inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.
10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.
12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – Shale Green , Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.
13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.
14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline

15. Any cultural and/or paleontological resource (historic or prehistoric site or object)

route is not used as a roadway.

discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

C. ELECTRIC LINES – Not applied for in APD

IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared; these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

Species	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	11bs/A
Four-winged Saltbush	5lbs/A

^{*}Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed