

km

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-05024
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-1613
7. Lease Name or Unit Agreement Name Brinson State
8. Well Number 2
9. OGRID Number 013837
10. Pool Name or Wildcat Grayburg Jackson SR Q G SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	<b>RECEIVED</b> JUN - 8 2010 NMOCD ARTESIA
2. Name of Operator Mack Energy Corporation	
3. Address of Operator P.O. Box 960 Artesia, NM 88210	
4. Well Location Unit Letter <u>A</u> <u>330</u> feet from the <u>North</u> line and <u>990</u> feet from the <u>East</u> line Section <u>36</u> Township <u>16S</u> Range <u>31E</u> NMPM County <u>Eddy</u>	
11. Elevation (Show whether DR, RKB, RT, GR etc.) 4129' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIALWORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Notify OCD 24 hours prior to starting plugging operations

- 1) Set CIBP @ 3800' w/ a 35' cmt cap
- 2) Set 25sx cmt plug from 3750-3594'.
- 3) Perforate 2200-2201' 4spf.
- 4) Establish circulation Pump 200sx Class C 14ppg, 1 19 yield.
- 5) Set 25sx plug from 2000-1870', WOC and tag. Base of Salt.
- 6) Set 25sx plug from 1000-870', WOC and tag Top of Salt & surface shoe.
- 7) Set plug from 65-0'. *Perf. + Spaz.*
- 8) Install P & A Marker

Note Circ well with salt gel mud consisting of at least 9 5# Brine with 25 pounds of gel per barrel after the bottom plug is set.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 6/4/10

Type or print name Jerry W. Sherrell E-mail address: jerrys@mec.com PHONE: (575) 748-1288

For State Use Only

APPROVED BY: [Signature] TITLE \_\_\_\_\_ DATE 6/8/2010


Conditions of Approval (if any):

Approval Granted providing work  
is complete by 9/8/2010

**Mack Energy Corporation**  
**Brinson State #2 30-015-05024**

**Before**

**After**



TOC @ 843'  
 8 5/8 csg @ 964'


TOC @ 2200'

7" casing @ 3710' cmt  
 w/100sx

TOC @ 3650'

Perfs 3855-3885'  
 4 1/2 liner from 3630-4008'  
 cmt w/200sx

TD 4232'



TOC @ 843'  
 8 5/8 csg @ 964'

TOC @ 2200'

7" casing @ 3710' cmt  
 w/100sx

TOC @ 3650'

Perfs 3855-3885'  
 4 1/2 liner from 3630-4008'  
 cmt w/200sx

TD 4232'

*Perf. ↓ Sgaz.*  
 cement plug from 65-0'

25sx plug from 1000-870'

25sx plug from 2000-1870'

Perf 2200-2201' squeeze 200sx  
 to surface

25sx plug from 3750-3594

CIBP @ 3800' w/35' cmt cap