Form 3160-5 (September 2001)

Oil Cons. UNITED STATES N.M. DIV-Dist. 2 FORM OMB N DEPARTMENT OF THE INTERIOR 1301 W. Grand Avenue Expires: J BUREAU OF LAND MANAGEMENT Artesia, NM 882 D Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposale

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

6. If Indian, Allottee or Tribe Name

adangoned we	II. US	se Form 3160-3 (APD)	tor sucn	oropos	ais.					
SUBMITIN TRIBLICATE: Other Instructions on rever						Law eggs 233	7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Other Other					RE	8. Well Name and No.				
2. Name of Operator								Keohane "C" Fed. #2		
Yeso Energy, Inc.				FER 0 4 2004			9. API Well No.			
3a. Address				3b. Phone No. (include great code)			30-015-26986 10. Field and Pool, or Exploratory Area			
P.O. Box 2248 Roswell, NM 88202 505-62 4. Location of Well (Footage, Sec., T, R., M., or Survey Description)				2-7355	-/355			Shugart; Y, SR, Q, GB		
330' FSL & 330' FEL Sec 21-T18S-R31E	-,,	,,					11. County	or Pari	ish, State	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE 1						F NOTICE, R	lew Mexico HER DATA			
TYPE OF SUBMISSION TYPE OF ACTION										
 Notice of Intent ✓ Subsequent Report ✓ Final Abandonment Notice 	00000	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture New Con Plug and Plug Bac	nstruction Abando	==	Production (Start Reclamation Recomplete Temporarily Ab			Water Shut-Off Well Integrity Other	
Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready: April 7, 2003April 10, 2003. MIRU Workover rig. Lay down: MIRU BJ Services. Pump 100 b Class "C" cement + 1% CaCl2. F 3555'. Leave pressure on well over equipment from location. Build a Prepare to rip and reseed location	olved (al Aba for fina 3625' bls war bump ernigh	operations. If the operation indomment Notices shall be all inspection.) of 2 3/8" tubing, rods and atter down csg into perform cement at 14.8#/gal with ht. Remove csg swedge stall regulation dry hole in	esults in a m filed only aft I pump. atios 3555-7 yield of 1.32 and confirm	oltiple co er all reco 5 and es 2 cu/ft/s: csg full	empletion nuirements stablish in k. Squee of ceme	or recompletion is, including reclaring rection rate of 3 eze perfs to 500 nt. Cut off well onment witnesses	n a new intervention, have be a BPM at 25 psi leaving shead and and by Dunca	O psi. Solid cechors.	orm 3160-4 shall be filed one ompleted, and the operator has been small be filed one ompleted, and the operator has been small be filed one of the operator has been surface to the same of the filed one of the f	
14. 1 hereby certify that the foregoing Name (PrintedlTyped)	g is tr	ue and correct			-					
Gene Lee		0.		Title	L	Agent				
Signature	ı,	Lu d	5 0	Date	_	April 10, 2003				
		THIS SPACE IF	OR FEDER	AL OR	STATE	OFFICE USE				
Approved by (Signature)		A RECORD			Name (Printed/Ty	ped)		Title		
Conditions of approval, if any, are attached. Approval of this notice does not want certify that the applicant holds legal or equipole title to those rights in the subject which would entitle the applicant to conduct operations thereon.				rrant or	Office				Date	
Title 18 U.S.C. Section 1001 and Ti States any false, fictitious or fraudule	tle 43 ent stat	U.S.C. Section 1212, make it ements or representations as	it a crime for to any matter	any pers	on knowir is jurisdict	ngly and willfully	to make to an	y depar	tment or agency of the Unite	