Office		t New Me		Form C-103
District I	Energy, Minerals	s and Natu	ral Resources	October 13, 2009 WELL API NO.
1625 N French Dr., Hobbs, NM 88240 District II	OIL CONGERNATION PROJECTS			30-005-61818
1301 W Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION			5. Indicate Type of Lease	
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410			STATE S FEE	
District IV Santa Fe, NM 87505 1220 S. St. Francis Dr., Santa Fe, NM 87505 87505			6. State Oil & Gas Lease No. V-132	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS T DIFFERENT RESERVOIR. USE "APPLICATION PROPOSALS)				Roadrunner VY State
1. Type of Well: Oil Well Gas Well Other				8. Well Number
2. Name of Operator		RECEIVED		9. OGRID Number
Yates Petroleum Corporation		JUN 2 9 2010 NMOCD ARTESIA		025575
3. Address of Operator				10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210				Pecos Slope; Abo
4. Well Location				
Unit Letter O: 660				1980 feet from the <u>East</u> line
	ownship 8S	Range		NMPM Chaves County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4007' GR				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A				
	LTIPLE COMPL		CASING/CEME	NT JOB
DOWNHOLE COMMINGLE			·	
OTHER:	•	П	OTHER:	,
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
6/08/10 MIRU. Loaded casing. Tested to 500 psi – held good. Released pkr. Nippled up BOP. TOH w/tbg. Set CIBP @ 4744' w/35'				
cement. WOC.				
6/11/10 thru 6/13/10 Loaded hole w/65 bbls mud gel. Perforated 4 holes @ 2595'. Loaded casing & tested to 500 psi. Could not pump				
into perfs. Spotted 25 sx Cl "C" cement @ 2645'. Tagged plug @ 2336'. Perforated 4 holes @ 1250'. Pumped 50 sx Cl "C" cement down casing. WOC. Tagged plug @ 1031'. Perforated 4 holes @ 60'.				
6/14/10 Circulated 20 sx Cl "C" cement from 60' to surface.				
6/15/10 Cut off wellhead, installed dry hole marker & cleaned location. WELL IS PLUGGED & ABANDONED.				
				,
Sand Date:	piα	Palaga Da	to	
Spud Date:	Kig	Release Da	le:	
I hereby certify that the information above	is true and compl	ete to the be	est of my knowled	lge and belief.
	-			
SIGNATURE Allows O	Ton TI	ITLE <u>Re</u>	gulatory Complia	nce Technician DATE 6/24/10
Type or print name Allison Barton E-mail address: abarton@yatespetroleum.com PHONE: (575) 748-1471 .				
For State Use Only		Translate W	for plugging of well be nder bond is retained Sunsequent Report of	Well Plugging)
APPROVED BY: Marke	TIT C	1 FOLC 193 (CD W	eb Page under DATE (30 2011)
Conditions of Approval (if any):		Lotair MA	w.cmnrd.state.nm.us	//000.