Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

On Marian

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Date 02/04/2004

Submit in Triplicate - Other instructions on reverse side. 1. Type of Well Other Submit in Triplicate - Other instructions on reverse side. 2. He into CA/Agreement, Name and/or No. 1. Type of Well Gas Well Other Submit in Triplicate - Other instructions on reverse side. 3. He into CA/Agreement, Name and/or No. 4. He into CA/Agreement, Name and/or No. 4. He into CA/Agreement, Name and/or No. 5. PEDERAL N 5. PED	SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				5. Lease Serial No. NMNM71752		
Type of Well Gias Well Other State Other O					6. If Indian, Allottee or Tribe Name		
Golf Well Golfast Well Other FEDERAL N 1	SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.		
2. Name of Operator DEVON ENERGY PRODUCTION COLP Contact: RONNIE SLACK E-Mail: ronnie-sland(gdvn.com 3 - Address 20 NORTH BROADWAY SUITE 1500 OKLAHOMA CITY, OK 73102 Ph: 405,552,4615 Sec 6 T22S R26E SWSW 467FSL 660FWL Sec 6 T22S R26E SWSW 467FSL 660FWL TYPE OF SUBMISSION Acidize Subsequent Report Casing Repair Change Plans Pina de Abandonment Notice Change Plans Pina de Abandon Completed Change Plans Ping and Abandon Completed Construction Ping and Abandon Completed Change Plans Ping and Abandon Completed Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete hortzontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. It is proposal is to deepen directionally or fried pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete hortzontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. If the proposal is to deepen directionally or fried pertainer results in a multiple completion or the number of fried pertainer results in a multiple completion or the number of fried pertainer results in a multiple completion or the number of fried pertainer results in a multiple completion or the number of fried pertainer results in a multiple completion or the number of marker. Set CIBP @ +/- 8460'. Cap with 50' comment. 2. Displace hole with 59 5 pp mud. 3. Cut 5-1/2" casing @ +/- 4300'. Pull casing. Note: Top of cement behind 5-1/2" casing @ 4320' per CBL. 4. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 5. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 6. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 7. Set surface cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 8. Set c	1. Type of Well						
DEVON ENERGY PRODUCTION COL P E-Mait: ronnie slackg@wn.com 30-015-25965-00-S3 3. Address CNCLAHOMA CITY, OK 73102 4. Location of Well (Foolinge, Sec., T. R. M., or Survey Description) Sec 6 T22S R26E SWSW 467FSL 660FWL TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Alter Casing Pepars Alter Casing Pepars New Construction Recomplete Casing Repair New Construction Recomplete Casing Repair New Construction Recomplete Casing Repair New Construction Recomplete Other Tipe In Abandonment Notice Casing Repair New Construction Recomplete Other Tipe In Abandonment Notice Casing Repair New Construction Recomplete Other Disposal is to despen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond Mo. on If with BLMSUIA. Required subsequent reports shall be filled within 30 days testing has been completed. Final Abandonnent Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection With 5.5 ppg ming for final Abandonnent Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined with 5.5 ppg ming for final allocations of the With Ming for the With S.5 ppg ming for final Abandonnent Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined with 5.5 ppg ming for final final for Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined with 5.5 ppg ming for final final fi	☐ Oil Well ☑ Gas Well ☐ Other						
20 NORTH BROADWAY SUITE 1500 Ph: 405.552.4615							
Sec 6 T22S R26E SWSW 467FSL 660FWL PFR 0 5 7004 EDDY COUNTY, NM	20 NORTH BROADWAY SUI	Ph: 405.552.4615 Fx: 405.552.1415		10. Field and Pool, or Exploratory HAPPY VALLEY			
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Acidize	4. Location of Well (Footage, Sec., T	RECEIVED		11. County or Parish, and State			
TYPE OF SUBMISSION Acidize	Sec 6 T22S R26E SWSW 467	FFR	0 5 7004	EDDY COUNTY, NM			
TYPE OF SUBMISSION Acidize			OCD-	ARTESIA			
Notice of Intent	12. CHECK APPI	ROPRIATE BOX(ES) TO	0 • =			ER DATA	
Notice of Intert Alter Casing Fracture Treat Reclamation Well Integrity Subsequent Report Casing Repair New Construction Recomplete Other Final Abandonment Notice Change Plans Plug and Abandon Temporarily Abandon Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM*PiA. Required subsequent reports shall be filed within 30 days following completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 1. Set CIBP @ +/- 6460'. Cap with 50' cement. 2. Displace hole with 9.5 ppg mud. 3. Cut 5-1/2' casing @ +/- 4300'. Pull casing. Note: Top of cement behind 5-1/2'' casing @ 4320' per CBL. 4. Set cement plug @ +/- 4200' to 4400'. WOC. Tag plug. 5. Set cement plug @ +/- 2500' to 550'. WOC. Tag plug. 6. Set cement plug @ +/- 2500' to 550'. WOC. Tag plug. 7. Set surface cement plug from 0 to 60. WOC. 8. Cut casing off 3 below ground level and install dry hole marker. 9. Backfill pits and restore location APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED 14. I hereby certify that the foregoing is true and correct. Electronic Submission #27476 verifies by the BLM Well Information System For DEVON ENERGY PRODUCTION CO L. P., sent to the Carlsbad Committed to AFMSS for processing by ARMANDO LOPEZ or 2002/2004 (04AL0084SE) Title ENGINEERING TECHNICIAN	TYPE OF SUBMISSION	TYPE OF ACTION					
Subsequent Report Casing Repair New Construction Recomplete Other Recomplete Other Recomplete Casing Repair New Construction Recomplete Other Recomplete Casing Repair Repair Report Recomplete Other Recomplete Casing Repair Repair Recomplete Casing Repair Recomplete Recomplete Casing Repair Recomplete Recomplete Casing Repair Recomplete Casing Repair Recomplete Recomplete Casing Repair Recomplete Recomplete Casing Repair Recomplete Recomplete Casing Recomplete Casing Recomplete Recomplete Recomplete Casing Recomplete Recomp	52 Notice of Intent	☐ Acidize	☐ Deepen	☐ Produc	tion (Start/Resume)	☐ Water Shut-Off	
Second Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLMR9IA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandomment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 1. Set CIBP @ +/- 6460'. Cap with 50' cement. 2. Displace hole with 9.5 ppg mud. 3. Cut 5-1/2" casing @ +/- 4200' to 4400'. WOC. Tag plug. 5. Set cement plug @ +/- 4200' to 4400'. WOC. Tag plug. 6. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 7. Set surface cement plug from 0 to 60 . WOC. 8. Cut casing off 3 below ground level and install dry hole marker. 9. Backfill pits and restore location 14. Thereby certify that the foregoing is true and correct. Electronic Submission #27476 verified by the BLM Well Information System For DEVON ENERGY PRODUCTION COL P., sent to the Carisbad Committed to AFMSS for processing by ARMANDO LOPEZ on 02/02/2004 (04AL0084SE) Name (PrintedTyped) RONNIE SLACK Title ENGINEERING TECHNICIAN Signature (Electronic Submission) Date 02/02/2004		☐ Alter Casing	☐ Fracture Treat ☐ Reclan		nation	■ Well Integrity	
Convert to Injection Plug Back Water Disposal	☐ Subsequent Report	☐ Casing Repair	r New Construction Recom		plete	☐ Other	
13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed oning a following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 1. Set CIBP @ +/- 6460'. Cap with 50' cement. 2. Displace hole with 9.5 ppg mud. 3. Cut 5-1/2" casing @ +/- 4300'. Pull casing. Note: Top of cement behind 5-1/2" casing @ 4320' per CBL. 4. Set cement plug @ +/- 2500' to 2400'. WOC. Tag plug. 5. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 6. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 7. Set surface cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 8. Cut casing off 3 below ground level and install dry hole marker. 9. Backfill pits and restore location 14. I hereby certify that the foregoing is true and correct. Electronic Submission #27476 verifies by the BLM Well Information System For DevOn Energy Production Co L. P., sent to the Carlsbad Committed to AFMSS for processing by ARMANDO LOPEZ on 02/02/2004 (04AL0084SE) Name (Printed/Typed) RONNIE SLACK Title ENGINEERING TECHNICIAN Date 02/02/2004	☐ Final Abandonment Notice	☐ Change Plans	☑ Plug and Abandon ☐ Tempo		rarily Abandon		
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed. Final Abandoment Notices shall be filed once testing has been completed, and the operator has determined that the site is ready for final inspection.) 1. Set CIBP @ +/- 6460'. Cap with 50' cement. 2. Displace hole with 9.5 ppg mud. 3. Cut 5-1/2" casing @ 4320' per CBL. 4. Set cement plug @ +/- 4200' to 4400'. WOC. Tag plug. 5. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 6. Set cement plug @ +/- 2500' to 550'. WOC. Tag plug. 7. Set surface cement plug @ +/- 350' to 550'. WOC. Tag plug. 8. Set cement plug @ +/- 350' to 550'. WOC. Tag plug. 9. Backfill pits and restore location 14. I hereby certify that the foregoing is true and correct. Electronic Submission #27476 verified by the BLM Well Information System For DeVON ENERGY PRODUCTION CO L. P., sent to the Carlsbad Committed to AFMSS for processing by ARMANDO LOPEZ on 02/02/2004 (04AL0084SE) Name (Printed/Typed) RONNIE SLACK Title ENGINEERING TECHNICIAN Date 02/02/2004		☐ Convert to Injection	☐ Plug Back ☐ Water 1		Disposal		
Electronic Submission #27476 verified by the BLM Well Information System For DEVON ENERGY PRODUCTION CO L P, sent to the Carlsbad Committed to AFMSS for processing by ARMANDO LOPEZ on 02/02/2004 (04AL0084SE) Name (Printed/Typed) RONNIE SLACK Title ENGINEERING TECHNICIAN Signature (Electronic Submission) Date 02/02/2004	If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 1. Set CIBP @ +/- 6460'. Cap with 50' cement. 2. Displace hole with 9.5 ppg mud. 3. Cut 5-1/2" casing @ +/- 4300'. Pull casing. Note: Top of cement behind 5-1/2" casing @ 4320' per CBL. 4. Set cement plug @ +/- 4200' to 4400'. WOC. Tag plug. 5. Set cement plug @ +/- 2500' to 2700'. WOC. Tag plug. 6. Set cement plug @ +/- 350' to 550'. WOC. Tag plug. 7. Set surface cement plug from 0 to 60 . WOC. 8. Cut casing off 3 below ground level and install dry hole marker. 9. Backfill pits and restore location APPROVAL SUBJECT TO GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED						
Name (Printed/Typed) RONNIE SLACK Signature Committed to AFMSS for processing by ARMANDO LOPEZ on 02/02/2004 (04AL0084SE) Title ENGINEERING TECHNICIAN Date 02/02/2004	14. I hereby certify that the foregoing is	Electronic Submission #					
Signature (Electronic Submission) Date 02/02/2004	Con						
	Name (Printed/Typed) RONNIE S	SLACK	Title ENGI	NEERING TE	ECHNICIAN		
	Signature (Electronic S	Submission)	Date 02/02	/2004			
	THIS SPACEFOR FEDERAL OR STATE OFFICE USE						

Approved By ALEXIS C SWOBODA Conditions of approval, if any, are attached. Approval this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

TitlePETROLEUM ENGINEER

Office Carlsbad