

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	2. NAME OF OPERATOR Enron Oil & Gas Company	3. ADDRESS OF OPERATOR P. O. Box 2267, Midland, Texas 79702	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 1980' FWL	5. PERMIT NO. 30-015-23069	6. ELEVATIONS (Show whether DT, RT, CR, etc.) 3642.5' GR	7. LEASE AGREEMENT NAME Canadian Kenwood Federal	8. FARM OR LEASE NAME Shugart, North Morrow	9. WELL NO. 1	10. FIELD AND POOL, OR WILDCAT Shugart, North Morrow	11. SEC., T., R., OR B.L.E. AND SUBST. OR AREA Sec. 17, T18S, R31E	12. COUNTY OR PARISH Eddy	13. STATE NM
--	--	--	---	-------------------------------	---	---	--	------------------	---	---	------------------------------	-----------------

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

DEEPEN OR ALTER CASING
MULTIPLE COMPLETION
ABANDON
CHANGE PLANT

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

*NOTIFY BLM @ (505) 887-6544 prior to commencing P&A operations.

1. TOH w/tubing and packer. TIH w/tbg open-ended and spot 25 sacks cement at 11,550'. WOC and tag. Circulated hole with mud-laden fluid.

→ Spot ±100' across top of Wolfcamp @ ±9470'.

2. Free-point, cut & pull 5-1/2" casing. Anticipated recovery = 7000'.

3. TIH w/tbg and spot 40 sx cement plug 50' below casing cutoff. [TAG PLUG] to extend 75' above/below csq. cut

4. Spot 40 sack plug 4469 to 4569 feet. [TAG PLUG].

5. Spot 35 sack plug 615 to 715 feet.

6. Spot 10 sacks at surface.

*use 10.0# mud-laden fluid to plug well.

→ all additions and deletions by SJS/ham.

18. I hereby certify that the foregoing is true and correct

SIGNED

Betty Seldon

TITLE Regulatory Analyst

DATE 11/9/88

(This space for Federal or State office use)

APPROVED BY OR'S SCD, PALO DRI
CONDITIONS OF APPROVAL, IF ANY, SOURCES

TITLE

DATE

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.