


Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-28863
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NW STATE
8. Well Number #33
9. OGRID Number 255333
10. Pool name or Wildcat: (3230) Artesia, Queen, Grayburg, San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3690' GL



SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location
Unit Letter H : 1728 feet from the NORTH line and 916 feet from the EAST line
Section 32 Township 17-S Range 28-E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Recomplete to San Andres & Squeeze Behind Csg ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 6/23/10, a CBL was run in this well indicating TOC @ ~2780'.

Lime Rock would like to place cmt behind the 5-1/2" csg as follows: Perf the 5-1/2" csg @ about 2755'-60', set a 5-1/2" cmt ret @ ~2720' & SQ the perms w/cmt as required to bring cmt to surface behind the 5-1/2" csg. The cmt retainer & cmt will be drilled out & the well CO to 3300'.

Lime Rock would also like to recomplete this well into the Artesia, Queen, Grayburg, San Andres (3230) as follows: Set a CIBP @ 3290' & top w/35' cmt. PT 5-1/2" csg to ~2000 psi for 30 min. Perf lower San Andres @ between ~2674'-2952'. Treat lower SA w/about 2500 gal acid & frac w/about 169,500# sand in X-linked gel. Set a 5-1/2" RBP @ ~2660'. PT 5-1/2" csg to ~2000 psi for 30 min. Perf middle SA between about 2465'-2631'. Treat middle SA w/~2500 gal HCL acid & frac w/about 165,000# sand in X-linked gel. Land 2-7/8" 6.5# J-55 tbg @ about 2960'. Run rods & pump & completed as a single San Andres oil well.

Spud Date: 3/17/96

Drilling Rig Release Date: 4/14/96

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 7/8/10

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 7/12/2010

Conditions of Approval (if any):