Form 3160-5 (April 2004)

IV.IVI. UII Cons. DIV-Dist. 2

DEPARTMENT OF THE INTERIOR 301 W. Grand Avenue

FORM APPROVED OMB NO. 1004-0137 Expires March 31, 2007

BUREAU OF LAND MANAGEMENT Artesia, NM 882105. Lease Serial No.

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
--------	---------	-----	---------	----	-------

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

Expires March 31, 200 ease Serial No.

6. If Indian, Allottee or Tribe Name

NM NM 112249

abandoned well. Use Form	n 3160-3 (APD) for	such proposals.			
SUBMIT IN TRIPLICATE -	Other instructions	TRECEIVE	ED	1	A/Agreement, Name and/or No
1 Type of Well Oil Well X Gas Well Other		AUG 1 3 201	0	8. Well Name	
2. Name of Operator PARALLEL PETROLEUM LLC	f	NMOCD ARTE	ESIA	FUNNY CIDE FED COM 9. API Well No	2 1525-8 1H
3a. Address 1004 N BIG SPRING, SUITE 400, MIDLA	ND, TX 79701	3b Phone No. (<i>include are</i> 432-685-6563	a code)	30-005-639	
4. Location of Well (Footage, Sec., T, R., M., or Survey I SL: 1880 FSL & 208 FEL, SEC 8, T15S BL: 1760 FSL & 1232 FWL, SEC 8, T15	, R25E			WALNUT CRE 97631 11 County or CHAVES	r Parish, State
12. CHECK APPROPRIATE	BOX(ES) TO INDI	CATE NATURE OF N	OTICE, REF	PORT, OR OT	HER DATA
TYPE OF SUBMISSION		TYP	E OF ACTION	I	
Notice of Intent X Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection		Reclamat Recomple Temporat X Water Di	ete rily Abandon sposal	Water Shut-Off Well Integrity Other
13 Describe Proposed or Completed Operation (clearly	v state all pertinent details	s, including estimated starting	g date of any p	roposed work and	approximate duration thereof.

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

AS PER YOUR REQUEST FOR ADDITIONAL INFORMATION, PIEASE SEE ATTACHMENT WITH ITEMS 1 THRU 7 ADDRESSED

Accepted for record NMOCD RF 8/17/10

SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	`itle	
KAYE MC CORMICK	SR PROD & REG TECH	
Louse My Comile	Date 06-30-2010	
THIS SPACE FOR FEDERAL	OR STATE OFFICE USE	
Approved by /S/ DAVID R. GLASS	Title PETROLEUM ENGINEER	AUG 0 4 2010
Conditions of approval, if any, are attached Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject least which exist the applicant to another transfer the subject to the subject to another transfer the subject to th		

WATER PRODUCTION & DISPOSAL INFORMATION

FOLLOWING FOR: Funny Cide 1H, API 30-005-63949

1. Name of formations producing water on the lease:

WOLFCAMP

2. Amount of water produced from all formations in barrels per day:

2.1 BWPD

3. Attach a current water analysis of produced water from all zones showing at least the total dissolved solids, ph and the concentrations of chlorides and sulfates. (One sample will suffice if water is commingled.)

PRODUCED WATER ANALYSIS DATED 06-22-2010 BY BJ CHEMICAL ATTACHED

4. How water is stored on lease.

ABOVE GROUND CLOSED TOP FIBERGLASS TANKS

5. How water is moved to the disposal facility.

TRANSPORTED BY COMMERCIAL TANK-TRUCK VENDOR

- 6. Identify the Disposal Facility by:
 - A. Facility Operators Name.

Mesquite SWD Inc.

B. Name of facility or well name and number

Ann SWD #001, API 30-015-23580

C. Type of facility or well (WDW) (WIW) etc.

DISPOSAL WELL (WDW)

D. Location by 1/4 1/4

1980 FNL & 1980 FEL, Unit G, Sec 18, T19S, R26E, Eddy Co.

7. Attach a copy of the State issued permit for the Disposal Facility.

COPY OF PERMIT APPROVAL ATTACHED

Submit to this office: ATTN: Linda Jimenez, Bureau of Land Management, 2909 West 2nd Street, Roswell, NM 88201, the above required information on a Sundry Notice 3160-5. Submit 1 original and 5 copies within abatement period. (This form may be used as an attachment to the Sundry Notice.) If you need further direction on this matter, feel free to call Linda Jimenez @ (575)-627-0263 (office)

Analytical Laboratory Report for:



PARALLEL PETROLEUM NM LEASES ONLY

Production Water Analysis

Listed below please find water analysis report from: Funny Cide, 1

Lab Test No:

2010130388

Sample Date:

06/22/2010

Specific Gravity: 1.046

TDS: pH:


69055

6.30

Cations:	mg/L	as:	
Calcium	3627	(Ca ^{⁺⁺})	,_
Magnesium	994	(Mg ⁺⁺)	
Sodium	21000	. o (Na ⁺)	
iron	48.00	(Fe ⁺⁺)	
Potassium	167.0	(K*)	
Barium	0.00	(Ba ^{⁺⁺})	
Strontium	80.00	(Sr ⁺⁺)	
Manganese	3.12	(Mn ⁺⁺)	
Anions:	mg/L	às:	
Bicarbonate	85	(HCO ₃)	
Sulfate	1950	(SO ₄ ⁼)	
Chloride	41100	(CI)	
Gases:			
Carbon Dioxide	100	(CO ₂)	
Hydrogen Sulfide	0	(H ₂ S)	

PARALLEL PETROLEUM NM Lab Test No: 2010130388 LEASES ONLY

DownHole SAT[™] Scale Prediction @ 100 deg. F



Mineral Scale	Saturation Index	Momentary Excess (ibs/1000 bbls)
Calcite (CaCO3)	0.30	-0.07
Strontianite (SrCO3)	0.01	-4.13
Anhydrite (CaSO4)	0.67	-510.95
Gypsum (CaSO4*2H2O)	0.89	-149.78
Barite (BaSO4)	0.00	-0.34
Celestite (SrSO4)	0.38	-216.90
Siderite (FeCO3)	6.08	0.03
Halite (NaCl)	ິ 0.01	-506412.47
Iron sulfide (FeS)	0.00	-0.32

Interpretation of DHSat Results:

The Saturation Index is calculated for each mineral species independently and is a measure of the degree of supersaturation (driving force for precipitation) under the conditions modeled. This value ranges from 0 to infinity with 1.0 representing a condition of equilibrium where scale will neither dissolve nor precipitate. Values less than 1.0 are undersaturated and values greater than 1.0 are supersaturated. The Momentary excess is a measure of how much scale would have to precipitate to bring the system back to a non-scaling condition. This value ranges from negative (dissolving) to positive (precipitating) values. The Momentary Excess represents the amount of scale possible while the Saturation Level represents the probability that scale will form.

Under the provisions of Rule 701(B), Ralph Nix made application to the New Mexico Oil Conservation Division on June 18, 1982, for permission to complete for salt water disposal its Ann Well No. 1 located in Unit G of Section 18, Township 19 South, Range 26 East, NMPM, Eddy County, New Mexico.

The Division Director finds:

- (1) That application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) That satisfactory information has been provided that all offset operators and surface owners have been duly notified; and
- (3) That the applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met.
- (4) That no objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED:

.That the applicant herein, Ralph Nix is hereby authorized to complete its Ann Well No. 1, located in Unit G of Section 18, Township 19 South, Range 26 East, NMPM, Eddy County, New Mexico, in such a manner as to permit the injection of salt water for disposal purposes into the Cisco Canyon formation at approximately 7770 feet to approximately 8110 feet through 2 7/8 inch plastic lined tubing set in a packer located at approximately 7750 feet.

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 1560 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Cisco Canyon formation.

That the operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment so that the same may be inspected.

That the operator shall immediately notify the supervisor of the Division's Artesia district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER, That jurisdiction of this cause is hereby retained by the Division for such further order or orders as may seem necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of applicant to comply with any requirement of this order after notice and hearing, the Division may terminate the authority hereby granted in the interest of conservation. That applicant shall submit monthly reports of the disposal operations in accordance with Rule 706 and 1120 of the Division Rules and Regulations.

Approved at Santa Fe, New Mexico, on this 13th of July, 1982.

STATE OF NEW MEXICO

OLL CONSERVATION DIVISION

JOE D. RAMEY,

Division Director

SEAL

BUREAU OF LAND MANAGEMENT

Roswell Field Office 2909 West Second Street Roswell, New Mexico 88201 575-627-0272

Disposal of Produced Water From Federal Wells Conditions of Approval

Approval of the produced water disposal methodology is subject to the following conditions of approval:

- 1. This agency shall be notified of any change in your method or location of disposal.
- 2. Compliance with all provisions of Onshore Order No. 7.
- 3. This agency shall be notified of any spill or discharge as required by NTL-3A.
- 4. This agency reserves the right to modify or rescind approval whenever it determines continued use of the approved method may adversely affect the surface or subsurface environments.
- 5. Any on-lease open top storage tanks shall be covered with a wire screen to prevent entry by birds and other wildlife.
- 6. This approval should not constitute the granting of any right-of-way or construction rights not granted by the lease instrument.
- 7. If water is transported via a pipeline that extends beyond the lease boundary, then you need to submit within 30 days an application for right-of-way approval to the Realty Section in this office for wells in Chaves or Roosevelt County if you have not already done so.