

Submit 1 Copy To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-21044
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-10167
7. Lease Name or Unit Agreement Name NDDUP Unit
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Dagger Draw; Upper Penn, North

RECEIVED

SEP 07 2010

NMOC D ARTESIA

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A ☐

2. Name of Operator  
Yates Petroleum Corporation

3. Address of Operator  
105 South Fourth Street, Artesia, NM 88210

4. Well Location  
Unit Letter A : 990 feet from the North line and 990 feet from the East line  
Section 16 Township 19S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3465' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/13/10 - NU BOP. POOH with tubing.

8/16/10 - Tagged up at 591'. RIH with gauge ring and junk basket to 7650'. Set a 5-1/2" 10K Alpha CIBP at 7600'. Tested casing to 500 psi, held good for 15 min.

8/17/10 - Tagged CIBP at 7600'. Pumped 25 sx Class "H" cement on top of CIBP. TOC at 7374'. Did not have to tag. Perforated 6 holes at 5817'. Pumped 55 sx Class "C" cement at 5680'. Est. TOC at 5590'.

8/18/10 - Tagged cement plug at 5475'. Pulled up to 4930'. Gun did not shoot. Perforated 4 holes at 4930'. Pumped 60 sx Class "C" cement. Lost circulation while pumping cement. Displaced cement to 4704' with 35.5 bbls mud. WOC 2-1/2 hrs. Tagged cement plug at 4512'. Perforated 4 holes at 2320'. Pumped 55 sx Class "C" cement. Displaced cement down to 2093' with 21.2 bbls mud. WOC 2 hrs. Tagged cement plug at 2040'. Tested casing to 500 psi, held good. Perforated 4 holes at 1200'. Pumped 50 bbls down casing. Did not break circulation. Was pumping into holes at 1200' at 2 BPM @ 700 psi. Pumped 50 sx Class "C" cement down casing. Displaced cement to 1025' with 23.7 bbls mud.

8/19/10 - Tagged cement plug at 1030'. Perforated 4 holes at 499'. Pumped 45 bbls down casing, would not circulate. Pumped 50 sx Class "C" cement. Displaced cement down to 250'. WOC 2 hrs. Tagged cement plug at 400'. Phil Hawkins with NMOC D said to pull up to 100' and perforate. Perforated 4 holes at 300'. Pumped 50 sx Class "C" cement. Displaced with 1.5 bbls to 65'. WOC 3 hrs. Did not tag cement. Pumped another 100 sx Class "C" cement. Displaced cement down to 100' with 2 bbls.

8/20/10 - Tagged cement plug at 302'. Circulated 93 sx Class "C" cement down 5-1/2" casing, up 8-5/8" surface. ND BOP. Dug out cellar and cut off wellhead. Installed dry hole marker. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE August 31, 2010

Type or print name Tina Huerta E-mail address tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Phil Hawkins TITLE Regulatory Compliance Supervisor DATE 9/8/2010

Conditions of Approval (if any):

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.