District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grånd Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 CLEZ July 21, 2008

For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.

Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Type of action: Permit Closure

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a closed-loop system that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, please submit a Form C-144.

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinan-

environment. Nor does approval refleve the operator of its responsibility to comply with	rany other applicable governmental authority strates, regulations of ordinances.
Operator: Yates Petroleum Corporation	OGRID #:025575
Address: 105 South Fourth Street, Artesia, New Mexico 88210	
Facility or well name: Oscuro BBC State Com #1H	
API Number: <u>30-015-38259</u> OCD Pern	it Number: 210913
U/L or Qtr/Qtr <u>E</u> Section <u>12</u> Township <u>25S</u> Ran	•
Center of Proposed Design: Latitude N 32.146483 Lon	gitude <u>₩ 104.151528</u> NAD: ☐1927 🔀 1983
Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotm	ent
2.	
☐ Closed-loop System: Subsection H of 19.15.17.11 NMAC	The AMERICA CONTROL OF THE COMMENT AND SHOW
Operation: Drilling a new well Workover or Drilling (Applies to activitie	
☐ Above Ground Steel Tanks or ☐ Haul-off Bins	1990 DECEMEN
Signs: Subsection C of 19.15-17.11 NMAC	RECEIVED
12"x 24", 2" lettering, providing Operator's name, site location, and emergen	by telephone numbers: NOV 12 2010
Signed in compliance with 19.15.3.103 NMAC	
4.	NMOCD ARTESIA
Closed-loop Systems Permit Application Attachment Checklist: Subsection Instructions: Each of the following items must be attached to the application. attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NM □ Operating and Maintenance Plan - based upon the appropriate requirement □ Closure Plan (Please complete Box 5) - based upon the appropriate require	Please indicate, by a check mark in the box, that the documents are AC s of 19.15.17.12 NMAC
Previously Approved Design (attach copy of design) API Number:	
Previously Approved Operating and Maintenance Plan API Number:	
Waste Removal Closure For Closed-loop Systems That Utilize Above Groun Instructions: Please indentify the facility or facilities for the disposal of liquids facilities are required.	
Disposal Facility Name: Gandy Marley	Disposal Facility Permit Number: <u>NM-01-0019</u>
Disposal Facility Name:CRI	Disposal Facility Permit Number: <u>R-9166</u> .
Disposal Facility Name: <u>Lea Land Farm</u>	Disposal Facility Permit Number: <u>WM-1-035</u>
Disposal Facility, Name: Sundance Services Inc.	Disposal Facility Permit Number: <u>NM-01-0003</u>
Will any of the proposed closed-loop system operations and associated activities Yes (If yes, please provide the information below) No	occur on or in areas that will not be used for future service and operations?
Required for impacted areas which will not be used for future service and operat Soil Backfill and Cover Design Specifications based upon the appropriat Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection	te requirements of Subsection H of 19.15.17:13 NMAC and 1 of 19.15.17.13 NMAC

oort.
than
=

Yates Petroleum Corporation Closed Loop System

Equipment Design Plan

Closed Loop System will consist of:

- 1 double panel shale shaker
- 1 (minimum) Centrifuge, certain wells and flow rates may require 2 centrifuges On certain wells, the Centrifuge will be replaced by a Clackco Settling Tank System
- 1 minimum centrifugal pump to transfer fluids
- 2-500 bbl. FW Tanks
- 1-500 bbl. BW Tank
- 1 half round frac tank 250 bbl. capacity as necessary to catch cement / excess mud returns generated during a cement job.
- 1 Set of rail cars / catch bins

Certain wells will use an ASC Auger Tank

Operation Plan

All equipment will be inspected at least hourly by rig personnel and daily by contractors' personnel.

Any spills / leaks will be reported to YPC, NMOCD, and cleaned up without delay.

Closure Plan

Drilling with Closed Loop System, haul off bins will be taken to Gandy Marley, Lea Land Farm, CRI or Sundance Services Inc.

Contingency Casing Design

If hole conditions dictate, 7" casing will be set at 6,600' MD (6,240' TVD). A 6 1/8" hole will then be drilled to 10,655' MD (6,240' TVD) where 4 1/2" casing will be set and cemented with one stage up to dv tool. After completion procedures, the 4 1/2" casing will be cut and pulled at 5700'.

		2n	d Inte	rmediate		_				
	0	ft	to	100	ft	Mal	ce up Torq	ue ft-lbs	Total ft =	100
O.D.	N	/eight		Grade	Threads	opt.	min.	mx.		
7 inches		26 #/fl	t	J-55	LT&C	3670	2750	4590		
Collapse Resistance	Inte	rnal Y	ield	Joint S	Strength	Body	/ Yield	Drift	1	
4,320 psi	4,980	psi	i	36	7 ,000 #	41	5 ,000 #	6.151		

	100 ft to	5,900 ft	Make up Torque ft-Ibs	Total ft = 5,80
O.D.	Weight	Grade Threads	opt. min. mx.	
7 inches	23 #/ft	J-55 LT&C	3130 2350 3	910
Collapse Resistance	Internal Yield	Joint Strength	I	Drift
3,270	4,360 psi	313 ,000 #	366 ,000 #	.25

	5,900 ft to	6,600 ft	Make up Torque ft-lbs	Total ft = 700
O.D.	Weight	Grade Threads	opt. min. mx.	
7 inches	26 #/ft	J-55 LT&C	3670 2750 4590	
Collapse Resistance	Internal Yield	Joint Strength	Body Yield Drift	1
4,320 psi	4,980 psi	367 ,000 #	415 ,000 # 6.151	

Stage I from 5400'-6,600': cement w/260sx Pecos Valley Lite (YLD 1.41 WT 13) TOC=5400'

Stage II from 1800'-5400': lead w/375sx Lite crete(YLD 2.66 Wt 9.9), tail w/100sx Pecos Valley Lite (YLD 1.41 WT 13) TOC=1800.'

Production

	0	ft	to	10,655	ft	١	/lake up Torq	ue ft-lbs	Total ft =	10,655
O.D.	We	eight		Grade	Threads	opt.	min.	mx.		
4.5 inches	11.	.6 #/ft		HCP-110	LT&C	302	0 2270	3780		
Collapse Resistance	Interi	nal Yie	1d	Joint S	trength		ody Yield	Drift	1	
8,650 psi	10,690	psi		279	# 000, 6		367 ,000 #	3.875		

DV tool placed at approx. 5700' and cemented with one stage up to dv tool. After completion procedures, the

Cemented w/510sx PVL (YLD 1.83 Wt 13) TOC= 5700'

^{4 1/2&}quot; casing will be cut and pulled at 5700'.

Tgt TVD: 6240.00	Tgt MD: 0.00	Tgt Displ.: 0.00	Method: Minimum Curvature
VS Az: 90.00	Tgt Radius: 0.00	Tgt N/S: 0.00	Tgt E/W: 4620.00
Units: Feet, °, 7100ft	Elevation:	Northing:	Easting:
Co: Yates Petroleum Corporation	Drillers: 0	Well Name: Oscuro BBC State Com. #1H	Location: Sect. 12, 25S-27E
	Units: Feet, °, 7100ft VS Az: 90.00	ates Petroleum Corporation Units: Feet, °, 7100ft VS Az: 90.00 Elevation:	Units: Feet, °, 9100ft VS Az: 90.00 Elevation: Tgt Radius: 0.00 Northing: Tgt N/S: 0.00

nents								<u>د</u>							,				٠	1
DLS 🐪 🎨		0.00 Castille	0.00 Top of Salt	0.00 Base of Salt	0.00 Bell Canyon	0.00 Cherry Canyon	0.00 Brushy Canyon	0.00 Brushy Canyon MK	0.00 KOP	12.00	12.00	12.00 Bone Springs	12.01	12.00	12.00	12.00	12.00	12.00	12.00 Avalon Shale Target	0.00 Lateral TD
**WR		0.00	0.00	0.00	00.0	0.00	00.0	0.00	1.56	0.00	0.00	0.00	00.0	0.00	00.00	0.00	0.00	0.00	0.00	00.00
BR		0.00	0.00	0.00	0.00	0.00	00.0	0.00	0.00	12.00	12.00	12.00	12.01	12.00	12.00	12.00	12.00	12.00	12.00	0.00
-, E/W-	00.00	0.00	0.00	0.00	0.00	0.00	00.00	0.00	0.00	1.47	19.65	20.22	57.83	114.36	186.76	271.87	365.96	464.92	477.46	4620.00
	00'0	0.00	00.00	0.00	00.0	0.00	00.0	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.01	0.00
, VS	00.0	00.00	00.0	00.00	00.00	00.00	00.00	00.00	0.00	1.47	19.65	20.22	57.83	114.36	186.76	271.87	365.96	464.92	477.46	4620.00
TVD	0.00	610.00	730.00	2160.00	2430.00	3230.00	4300.00	5550.00	5762.54	5799.96	5898.11	5900.04	5990.33	6072.60	6141.32	6193.48	6226.80	6239.84	6240.00	6240.01
Azi.	00.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00	90.00
· Juc.	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	4.49	16.49	16.73	28.50	40.50	52.50	64.50	76.50	88.50	90.00	90.00
CL:	0.00	610.00	120.00	1430.00	270.00	800.00	1070.00	1250.00	5762.54	37.46	100.00	139.48	97.98	100.00	100.00	100.00	100.00	100.00	750.00	4142.54
, OM 🤃	0.00	610.00	730.00	2160.00	2430.00	3230.00	4300.00	5550.00	5762.54	5800.00	5900.00	5902.02	00.0009	6100.00	6200.00	6300.00	6400.00	6500.00	6512.53	10655.07
No	0	_	2	်က	4	2	9	7	&	6	10	1	12	13	14	15	16	17	18	19

www.trantlogistics.com



