

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-02217
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-4397
7. Lease Name or Unit Agreement Name: East Millman Pool Unit Tract 1
8. Well Number 1
9. OGRID Number 019958
10. Pool name or Wildcat Millman Yates-SR-QN-GB-SA, East

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Water Injection
2. Name of Operator Stephens & Johnson Operating Co.
3. Address of Operator P.O. Box 2249, Wichita Falls, TX 76307-2249
4. Well Location Unit Letter <u>E</u> : <u>2310</u> feet from the <u>North</u> line and <u>330</u> feet from the <u>West</u> line Section <u>12</u> Township <u>19S</u> Range <u>28E</u> NMPM County <u>Eddy</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3414' KB, 3403' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☒
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC.. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11-04-10: Pull out of hole w/tbg and pkr.
11-05-10: Go in hole w/RBP and set at 1517' KB. Locate csg leak 23' from surface.
11-08-10: Backed off 4 1/2" csg at 97' and pull out of hole w/csg.
11-09-10: Go in hole w/2 full jts and one 15' jt of 4 1/2" csg and screw back into csg in hole. Remove RBP from hole and then clean out wellbore down to 1925'. Go in hole with Baker AD-1 pkr and 50 jts of Poly Lined tbg. Circulate pkr fluid and set pkr @ 1600'. Pressure test csg to 430 psig. Pressure increased to 435 psig in 30 minutes. Passed MIT, see attached pressure chart.



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Kincaid TITLE Petroleum Engineer DATE 11-22-2010
mkincaid@sjoc.net

Type or print name William M. Kincaid E-mail address: mkincaid@sjoc.net PHONE (940) 723-2166

For State Use Only

APPROVED BY Richard Inao TITLE Compliance Officer DATE 12/01/10
Conditions of Approval (if any):

