

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-015-28003 |
| 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No. |
| 7. Lease Name or Unit Agreement Name Tackitt AOT |
| 8. Well Number 2 |
| 9. OGRID Number 025575 |
| 10. Pool name or Wildcat N. Seven Rivers; Glorieta-Yeso |

| | |
|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other | |
| 2. Name of Operator Yates Petroleum Corporation | |
| 3. Address of Operator 105 South Fourth Street, Artesia, NM 88210 | |
| 4. Well Location Unit Letter <u>J</u> : <u>1980</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>East</u> line Section <u>28</u> Township <u>19S</u> Range <u>25E</u> NMPM <u>Eddy</u> County | |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3470'GR | |

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Plugback and recomplete ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/8/11 - NU BOP.

2/10/11 - Ran GR to a depth of 7570'. Set a 7" 26# CIBP at 7556' with 35' cement on top. Tested 7" casing from 7521' to surface. Tested to 1000 psi, held good.

2/13/11 - Spotted 35 sx Class "H" cement from 5953'-6162'. Spotted 35 sx Class "C" cement from 3736'-3945'.

2/14/11 - Perforated Yeso 2440'-2485' (41). Circulated hole with 3% KCL. Spotted 3 bbls acid at 2485'. Acidized with 5000g 15% NEFE DI acid with 85 ball sealers. Balled out with 60 balls on.

2/15/11 - ND BOP.

2/10/11 - Frac with a 25# Borate XL, 4677 bbls fluid, 141,220# 16/30 white sand, 48,100# 16/30 RCS. 2-7/8" 6.5# J-55 tubing at 2580'.

RECEIVED

MAR 08 2011

NMOCD ARTESIA

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE March 7, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: David Gray TITLE Field supervisor DATE 3-9-11

Conditions of Approval (if any):