Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	OCD- Artesia
-1	FORM APPROVED
1	OMB NO. 1004-0135
1	Expires: July 31, 2010

Lease Serial No.

NMNM124659

BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an

6 If Indian Allottee or Tribe Name

abandoned wel	II. Use form 3160-3 (APD	) for such p	roposals.		o. Il liulaii, Anottee	or tribe reame			
SUBMIT IN TRII	PLICATE - Other instruct		7. If Unit or CA/Agreement, Name and/or No.						
1. Type of Well ☐ Gas Well ☐ Oth	пет		***************************************	8. Well Name and No. BURTON 6 FEDERAL 1					
Name of Operator     CIMAREX ENERGY CO OF COMMANDER	RUEGER		9. API Well No. 30-015-38226-00-X1						
3a. Address		3b. Phone No.	(include area code	e)	10. Field and Pool, or		_		
600 E MARIENFELD ST SUI MIDLAND, TX 79701	D-1936 -1940		PARKWAY						
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)			11. County or Parish,	, and State				
Sec 6 T20S R30E NWNW 150		,		EDDY COUNTY, NM					
12. CHECK APPE	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF	NOTICE, RE	PORT, OR OTHE	ER DATA			
TYPE OF SUBMISSION		ТҮРЕ О	F ACTION		:	16			
☐ Notice of Intent	☐ Acidize	□ Deep	en	Production	on (Start/Resume)	☐ Water Shut-Off			
_	☐ Alter Casing	□ Fract	ture Treat	☐ Reclamat	tion	☐ Well Integrity			
Subsequent Report	☐ Casing Repair		Construction	□ Recompl		other Well Spud			
☐ Final Abandonment Notice	☐ Change Plans	Name of Street	and Abandon		rily Abandon	wen spuu			
13. Describe Proposed or Completed Ope	Convert to Injection	□ Plug		□ Water Di					
testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  10-28-10 Spudded 18.75 inch hole.  11-02-10 Ran 8 jts 16 inch 65# H40 BTC @ 330. Cmt with lead 100 sx Swiftcem, tail 240 sx Halcem, no rtns. TS TOC 250. One-inched with 142 sx Thixotropic.  11-03-10 Tagged @ 80. One-inched with 40 sx Thixotropic, returned 10 bbls cmt, cmt dropped. One-inched with 35 sx Thixotropic, no returns. One-inched with 50 sx Thixotropic, tagged @ 11. WOC 20 hrs. Tested to 1000# for 30 min, ok.  11-08-10 In 14.75 inch hole, ran 36 jts 11.75 inch 42# H40 STC @ 1605.  11-09-10 Cmt with lead 600 sx Extendacem, tail 225 sx Halcem C, circ 215 sx, WOC 40.5 hrs. Tested									
14. I hereby certify that the foregoing is  Con  Name (Printed/Typed) NATALIE	Electronic Submission #1 For CIMAREX ENER nmitted to AFMSS for proce	GY CO OF C	DLÓRADO, sem RT SIMMONS on	t to the Carlsba	ad	EIVEL 9 2011 ARTESIA	/		
Signature (Electronic S			Date 02/21/2			AM BO			
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE				
Approved By ACCEPT	ED		JAMES A TitleSUPERV			Date 02/26/20	111		
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to condition	uitable title to those rights in the	Office Carlsba	ad						
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a statements or representations as	crime for any pe to any matter w	erson knowingly ar	nd willfully to ma	ke to any department	or agency of the United			



## Additional data for EC transaction #102919 that would not fit on the form

## 32. Additional remarks, continued

to 1300# for 30 min, ok.

11-15-10 In 10.625 inch hole, ran 83 jts 8.625 inch 32# K55 LTC @ 3502. Cmt Stage 1 with lead 350 sx Econocem HLC, tail 215 sx Halcem. DVT @ 3502, no returns. Cmt Stage 2 with lead 400 sx Econocem, tail 100 sx Halcem, circ 212 sx, WOC 31 hrs. Tested to 1300# for 30 min, ok.

11-28-10 TD'd 7.875 inch pilot hole @ 8555.

11-30-10 Set 170 sx Class H cement plug from 7721-8304.

12-01-10 Drilled through cmt to 8080 and kicked off 7.875 inch lateral.

12-12-10 TD'd lateral @ 11795 MD, 8411 TVD.

12-16-10 Ran 309 jts 5.5 inch 17# P110 casing. LTC 0-7534, BTC 7534-8654, LTC 8654-11784. Cmt with lead 600 sx Econocem, tail 900 sx Versacem. Tested to 3000# for 30 min, ok. TOC surface.

12-18-10 Released rig.