

Submit 1 Copy To Appropriate District  
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

October 13, 2009

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-36220
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VB-793
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Shocker 32 State
4. Well Location Surface A : 330 feet from the North line and 330 feet from the East line BHL P : 330 feet from the South line and 380 feet from the East line Section 32 Township 25S Range 29E NMPM Eddy County		8. Well Number 3H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2983'GR		9. OGRID Number 025575
		10. Pool name or Wildcat Willow Lake; Bone Spring, Southeast

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETIONS ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPERATIONS ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/8/11 - TD 12-1/4" hole to 2890'. Set 9-5/8" 36# K-55 LT&C casing at 2890'. Cemented with 738 sx 35:65:6 Poz "C" + 40% D020 + 0.125#/sx D130 + 2% S001 (yld 1.97, wt 12.9). Tailed in with 200 sx 35:65:6 Poz "C" + 0.1% D201 (yld 1.33, wt 14.8). Circulated 57 sx to pit. NOTE: Notified Damaged Gray NMOCD-Artesia of running casing and cementing. Tested casing to 1000 psi for 30 min. WOC 24 hr 40 min. Reduced hole to 8-3/4" and resumed drilling.



Spud Date:

10/29/10

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Tina Huerta*

TITLE

Regulatory Compliance Supervisor

DATE

April 12, 2011

Type or print name

Tina Huerta

E-mail address:

tinah@yatespetroleum.com

PHONE:

575-748-4168

**For State Use Only**

APPROVED BY:

*Donald Gray*

TITLE

Field Supervisor

DATE

4-19-11

Conditions of Approval (if any):