

RECEIVED

OCT - 3 1950

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

OIL CONSERVATION COMMISSION  
HOBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

October 2, 1950

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

HONOLULU OIL CORPORATION State of New Mexico Well No. 5 in the

Company or Operator

Lease

SW/4 of NE/4 of Sec. 13, T. 11-S, R. 27-E, N. M. P. M.,

Chisum Field Chaves County.

The dates of this work were as follows: September 27, 1950

Notice of intention to do the work was (crossed out) submitted on Form C-102 on September 25, 1950

and approval of the proposed plan was (crossed out) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was plugged in following manner: 0-16', 5 sax cement; 15-2115', mud (10.1 lbs. per gallon); 2115-2200' 25 sax cement; 2200-6515' mud (10.1 lbs. per gallon); 6515-6600', 25 sax cement; 6600-6615' TD, mud (10.1 lbs per gallon). The 8-5/8" casing was cemented from the shoe (2195') to the surface and left in the well.

Witnessed by W. P. Von Osinski HONOLULU OIL CORPORATION Geologist  
Name Company Title

Subscribed and sworn before me this 2

I hereby swear or affirm that the information given above is true and correct.

day of October, 1950

Name George R. Hoy

N. F. Simpson Notary Public

Position Division Development Engineer

My commission expires June 1, 1951

Representing HONOLULU OIL CORPORATION

P. O. Drawer 1391

Address Midland, Texas

Remarks:

APPROVED  
OCT 3 1950

Roy Yankrass  
Name  
& Gas Inspector  
Title