

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Copy 7 SF  
Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 8365

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lynne Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec. 4, T-14-S, R-29-E

12. COUNTY OR PARISH 13. STATE

Chaves

N.M.

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Kingery Drilling Co., Inc. ✓

3. ADDRESS OF OPERATOR  
Box 1588, Ardmore, Okla.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980 FNL 660 FWL

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 3681

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
(Other) Plug back to run 5 1/2" Csg.

FILL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other) Running Csg.   
REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/3/70

Spudded 2:45 PM 6/3/70

6/4/70

Ran 9 joints (341') 8 5/8" 20# H-40 8R-R2 Csg. Cement at 350' with 200 sx Class "C" Cement with 2% Calcium Chloride. Plug down 1:00 AM 6/4/70 Circulate 20 sx. After WOC 18 hours tested casing with 600 psi. Test okay.

6/11/70

T.D. 2165', Spotted 25 sx (cm 1700' - 1600'). Ran 50 joints (1600') 15 1/2" 14# H-40 8R-R2 used casing. Cemented with 100 sx Class "C" cement. Plug down 3:00 PM 6/11/70. Tested casing with 1800 psi for 30 min. Test Okay.

RECEIVED

RECEIVED

JUN 16 1970

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD PURPOSES  
JUN 16 1970  
ACTING District Engineer

\*See Instructions on Reverse Side