

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

MAY - 4 1982

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. LG-335	
7. Unit Agreement Name	
8. Farm or Lease Name Springer TK State	
9. Well No. 2	
10. Field and Pool, or Wildcat Und. Pecos Slope Abo	
12. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

Name of Operator
Yates Petroleum Corporation /

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 4S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4043.6' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole 6:00 PM 4-29-82. Set 40' of 20" conductor pipe. Ran 24 joints of 10-3/4" 40.5# casing set at 964'. 1-Texas Pattern notched guide shoe at 964'. Insert float at 924'. Cemented w/400 sacks Pacesetter Lite 3% CaCl₂. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 7:00 AM 5-1-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out at 1:00 AM 5-2-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

PREPARED BY [Signature] TITLE Engineering Secretary DATE 5-4-82

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE MAY 6 1982

CONDITIONS OF APPROVAL, IF ANY: