


NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	✓	
FILE	✓	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	✓	

NEW MEXICO OIL CONSERVATION COMMISSION



Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-5349	
6. Unit Agreement Name	
7. Farm or Lease Name State S.E.	
8. Well No. 2	
9. Field and Pool, or Wildcat Undes. Four Ranch Pro-Don WOLF CAMP	
10. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. (APPLICABLE FOR PERMIT "A" FORM C-1011 FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/>	2. GAS WELL <input checked="" type="checkbox"/>	3. OTHER _____
4. Name of Operator ELK OIL COMPANY		
5. Address of Operator P. O. BOX 310, ROSWELL, NEW MEXICO 88201		
6. Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>9S</u> RANGE <u>26E</u>		
15. Elevation (Show whether DF, RT, GR, etc.) 3794 Grd.		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

16. Description of Current or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well on August 21, 1984. Drill 11" hole to 985'. Ran 985' of 24# 8 5/8" casing. Cemented w/350 sx Howco lite containing 1/4# flocele, 5# gilsonite, 9# salt and 200 sx Class "C" containing 1/4# flocele, 2% CaCl₂. Cement circulated. WOC 18 hours; tested casing to 1,000#, test OK. Resume drilling 7 7/8" hole.

I, the undersigned, hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: _____ TITLE President DATE 8/31/84

Original Signed By
Leslie A. Clements
Supervisor District #

APPROVED BY: _____ TITLE _____ DATE SEP 6 1984

CONDITIONS OF APPROVAL, IF ANY: