

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

+
cist
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED
JAN 13 1993
O. C. D.
ARTESIA

WELL API NO.
30-005-62936

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
LG 4334

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
Sparrow SP State

1. Type of Well:
OIL WELL GAS WELL OTHER

8. Well No.
5

2. Name of Operator
YATES PETROLEUM CORPORATION

9. Pool name or Wildcat
Pecos Slope Abo

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter N : 660 Feet From The South Line and 1980 Feet From The West Line
Section 5 Township 7S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3929' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON
TEMPORARILY ABANDON CHANGE PLANS
PULL OR ALTER CASING
OTHER:
SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING
COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
CASING TEST AND CEMENT JOB
OTHER: Set Production Casing, Perforate, Trt

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4200'. Reached TD 1-1-93. Ran 94 joints 4-1/2" 10.5# J-55 ST&C casing set 4200'. Float shoe set 4200', float collar set 4155'. Cemented w/375 sx PP Silicalite w/.8% Halad 322, .3% CFR 3, 10# Gilsonite, 1/2# Flocele (yield 1.57, wt 13.0). PD 12:30 AM 1-3-93. Bumped plug to 475 psi, float held OK. WOC 24 hrs. Ran 1" from 1600' to surface and cemented w/300 sacks cement. Perforated as follows: 3675-3833' w/16 - .42" holes. 3675-82' (8 holes-1 SPF), 3826-33' (8 holes-1 SPF). Acidized perfs in two stages w/2000 gals 7 1/2% NEFE acid. Frac'd perfs 3675-3833' w/40000 gals 30# linear gel and 80000# 20/40 brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-11-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)
ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR DISTRICT II TITLE _____ DATE JAN 13 1993
APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY: _____