

ARAPAHO OIL AND GAS  
CPU 21  
SEC. 3, T-17S, R-29E  
1980' FSL & 860' FEL  
EDDY COUNTY, NEW MEXICO  
SUBSEQUENT PLUGGING REPORT

7/26/93

TIH W/ tbg to 2,051' and spotted 55 sacks class C cement, POOH W, tbg and pressured to 150 PSI. Shut well in and shut down for night.

7/27/93

TIH and tagged cement at 1,963', circulated hole W/ salt gel, POOH W/ tbg.

Perforated 4 holes at 1,700', TIH W/ tbg and spotted 25 sack class C cement plug. POOH W/ Tbg and pressured to 150 PSI.

W.O.C. 3 hrs

TIH W/ sinker bar on wire line & tagged plug @ 1,430'. TIH W/ tbg to 1,140' and spotted 31 sack class C cement plug and brought top of cement to 850'.

Dug out surface casing head and broke out casing valve found that cement was at surface.

7/28/93

Cut off well head and spotted 10' surface plug, welded on P&A marker W/ following information welded on marker.

ARAPAHO OIL & GAS  
CPU 21  
SEC 3, T-17S,R-29E  
1980' FSL & 860' FEL

Location was cleaned and leveled.

Tommy W. Folsom  
Consultant